



*The Right Connection™*

## Brass Fittings

**KORD INDUSTRIAL INC. 866.874.5673**

### Brass Fittings



## Brass Short Shank Fittings - NPSM Thread

uses KRW washers on page 275

**complete machined coupling**

| Hose ID | Thread | Part #                    |
|---------|--------|---------------------------|
| 1/2"    | 3/4"   | <b>BS406</b>              |
| 3/4"    | 3/4"   | <b>BS606</b>              |
| 1"      | 1"     | <b>BS808</b> <sup>1</sup> |




**machined female with swivel nut**

| Hose ID | Thread | Part #                    |
|---------|--------|---------------------------|
| 1/2"    | 3/4"   | <b>BS446</b>              |
| 5/8"    | 3/4"   | <b>BS546</b>              |
| 3/4"    | 3/4"   | <b>BS646</b>              |
| 1"      | 1"     | <b>BS848</b> <sup>1</sup> |



**machined male**

| Hose ID | Thread | Part #                    |
|---------|--------|---------------------------|
| 1/2"    | 3/4"   | <b>BS416</b>              |
| 3/4"    | 3/4"   | <b>BS616</b>              |
| 1"      | 1"     | <b>BS818</b> <sup>1</sup> |



<sup>1</sup> NPSH threads

## GHT Thread Fitting with Hex Nut

**complete cast coupling** (sold in complete sets only)

| Hose Size | Brass Part #              |
|-----------|---------------------------|
| 1/2"      | <b>CBC74</b>              |
| 5/8"      | <b>CBC75</b>              |
| 3/4"      | <b>CBC76</b>              |
| 1"        | <b>CBC88</b> <sup>1</sup> |



<sup>1</sup> NPSM threads

**complete machined coupling**

| Hose Size | Brass Part # | 303 Stainless Part # |
|-----------|--------------|----------------------|
| 3/8"      | <b>BC73</b>  | ---                  |
| 1/2"      | <b>BC74</b>  | <b>SSC74</b>         |
| 5/8"      | <b>BC75</b>  | <b>SSC75</b>         |
| 3/4"      | <b>BC76</b>  | <b>SSC76</b>         |
| 1"        | <b>BC78</b>  | ---                  |



**machined female with swivel nut**

| Hose Size | Brass Part # | 303 Stainless Part # | Pkg Qty |
|-----------|--------------|----------------------|---------|
| 3/8"      | <b>BCF73</b> | ---                  | 25      |
| 1/2"      | <b>BCF74</b> | <b>SSCF74</b>        | 25      |
| 5/8"      | <b>BCF75</b> | <b>SSCF75</b>        | 25      |
| 3/4"      | <b>BCF76</b> | <b>SSCF76</b>        | 25      |
| 1"        | <b>BCF78</b> | ---                  | 10      |



**machined male**

| Hose Size | Brass Part # | 303 Stainless Part # | Price/E | Pkg Qty |
|-----------|--------------|----------------------|---------|---------|
| 3/8"      | <b>BCM73</b> | ---                  | ---     | 25      |
| 1/2"      | <b>BCM74</b> | <b>SSCM74</b>        | ---     | 25      |
| 5/8"      | <b>BCM75</b> | <b>SSCM75</b>        | ---     | 25      |
| 3/4"      | <b>BCM76</b> | <b>SSCM76</b>        | ---     | 25      |
| 1"        | <b>BCM78</b> | ---                  | ---     | 10      |



## GHT Adapters



female GHT swivel

| Female x Female | Brass        |  | Opt Qty |
|-----------------|--------------|--|---------|
|                 | Part #       |  |         |
| GHT x GHT       | <b>BA977</b> |  | 25      |



female GHT swivel x female NPTF

| Female x Female | Brass         |  | 303 Stainless              |  | Opt Qty |
|-----------------|---------------|--|----------------------------|--|---------|
|                 | Part #        |  | Part #                     |  |         |
| GHT x 1/2" NPTF | <b>BAS974</b> |  | <b>RAS974</b> <sup>1</sup> |  | 25      |
| GHT x 3/4" NPTF | <b>BAS976</b> |  | <b>RAS976</b> <sup>1</sup> |  | 10      |



female GHT swivel x male NPTF

| Female x Male   | Brass           |  | 303 Stainless                 |     | Opt Qty |
|-----------------|-----------------|--|-------------------------------|-----|---------|
|                 | Part #          |  | Part #                        |     |         |
| GHT x 1/4" NPTF | <b>504-1204</b> |  | ---                           | --- | 25      |
| GHT x 3/8" NPTF | <b>504-1206</b> |  | ---                           | --- | 25      |
| GHT x 1/2" NPTF | <b>504-1208</b> |  | <b>R504-1208</b> <sup>1</sup> |     | 25      |
| GHT x 3/4" NPTF | <b>504-1212</b> |  | <b>R504-1212</b> <sup>1</sup> |     | 25      |



female GHT x male NPTF

| Female x Male   | Brass         |  | 303 Stainless              |     | Opt Qty |
|-----------------|---------------|--|----------------------------|-----|---------|
|                 | Part #        |  | Part #                     |     |         |
| GHT x 3/8" NPTF | <b>BMA973</b> |  | ---                        | --- | 25      |
| GHT x 1/2" NPTF | <b>BMA974</b> |  | <b>RMA974</b> <sup>1</sup> |     | 25      |
| GHT x 3/4" NPTF | <b>BMA976</b> |  | <b>RMA976</b> <sup>1</sup> |     | 25      |



rigid female GHT x female NPTF

| Female x Female | Brass        |  | 303 Stainless             |     | Opt Qty |
|-----------------|--------------|--|---------------------------|-----|---------|
|                 | Part #       |  | Part #                    |     |         |
| GHT x 1/8" NPTF | <b>BA971</b> |  | ---                       | --- | 50      |
| GHT x 1/4" NPTF | <b>BA972</b> |  | ---                       | --- | 25      |
| GHT x 3/8" NPTF | <b>BA973</b> |  | ---                       | --- | 25      |
| GHT x 1/2" NPTF | <b>BA974</b> |  | <b>RA974</b> <sup>1</sup> |     | 25      |
| GHT x 3/4" NPTF | <b>BA976</b> |  | <b>RA976</b> <sup>1</sup> |     | 25      |



threaded male

| Male x Male   | Brass                        |  | 303 Stainless             |     | Opt Qty |
|---------------|------------------------------|--|---------------------------|-----|---------|
|               | Part #                       |  | Part #                    |     |         |
| GHT x GHT     | <b>BA777</b> <sup>2</sup>    |  | <b>RA777</b> <sup>1</sup> |     | 25      |
| 1" NPSH x GHT | <b>509-1612</b> <sup>2</sup> |  | ---                       | --- | 20      |



male GHT x male NPTF

| Male x Male     | Brass                       |  | 303 Stainless             |     | Opt Qty |
|-----------------|-----------------------------|--|---------------------------|-----|---------|
|                 | Part #                      |  | Part #                    |     |         |
| GHT x 3/8" NPTF | <b>BA73</b> <sup>2</sup>    |  | ---                       | --- | 25      |
| GHT x 1/2" NPTF | <b>BA74</b> <sup>2</sup>    |  | <b>RA74</b> <sup>1</sup>  |     | 25      |
| GHT x 3/4" NPTF | <b>BA776</b> <sup>2,3</sup> |  | <b>RA776</b> <sup>1</sup> |     | 25      |
| GHT x 1" NPTF   | <b>BA78</b> <sup>2</sup>    |  | ---                       | --- | 10      |



male GHT x female NPTF

| Male x Female   | Brass                        |  | 303 Stainless             |         | Opt Qty |
|-----------------|------------------------------|--|---------------------------|---------|---------|
|                 | Part #                       |  | Part #                    | Price/E |         |
| GHT x 1/4" NPTF | <b>507-1204</b> <sup>2</sup> |  | ---                       | ---     | 25      |
| GHT x 3/8" NPTF | <b>507-1206</b> <sup>2</sup> |  | ---                       | ---     | 25      |
| GHT x 1/2" NPTF | <b>BA794</b> <sup>2</sup>    |  | <b>RA794</b> <sup>1</sup> |         | 25      |
| GHT x 3/4" NPTF | <b>BA796</b> <sup>2</sup>    |  | <b>RA796</b> <sup>1</sup> |         | 25      |



garden hose cap

| Female | Brass       |         | Opt Qty |
|--------|-------------|---------|---------|
|        | Part #      | Price/E |         |
| GHT    | <b>GHC7</b> |         | 25      |

<sup>1</sup> stainless steel fittings are NPT<sup>2</sup> redesigned with extended male GHT, deeper thread<sup>3</sup> BA776 also has 1/2" female NPT on ID of 3/4" male NPT side

## Adapters

## hex nipples

• ref SAE 130137

| NPTF Thread | Brass Part #  |  | Opt Qty |
|-------------|---------------|--|---------|
| 1/8" x 1/8" | <b>BCN12</b>  |  | 100     |
| 1/4" x 1/4" | <b>BCN25</b>  |  | 100     |
| 3/8" x 3/8" | <b>BCN37</b>  |  | 50      |
| 1/2" x 1/2" | <b>BCN50</b>  |  | 25      |
| 3/4" x 3/4" | <b>BCN75</b>  |  | 25      |
| 1" x 1"     | <b>BCN100</b> |  | 10      |



## hex head plugs

| NPT Thread | Brass Part # |  |  |
|------------|--------------|--|--|
| 1/8"       | <b>HHP1M</b> |  |  |
| 1/4"       | <b>HHP2M</b> |  |  |
| 3/8"       | <b>HHP3M</b> |  |  |
| 1/2"       | <b>HHP4M</b> |  |  |
| 3/4"       | <b>HHP6M</b> |  |  |
| 1"         | <b>HHP8M</b> |  |  |



• hex head plug is hollow

## square head plugs

| NPT Thread | Brass Part #     |  | Opt Qty |
|------------|------------------|--|---------|
| 1/8"       | <b>211-0200C</b> |  | 50      |
| 1/4"       | <b>211-0400C</b> |  | 100     |
| 3/8"       | <b>211-0600C</b> |  | 25      |
| 1/2"       | <b>211-0800C</b> |  | 25      |
| 3/4"       | <b>211-1200C</b> |  | 25      |



## male unions

| NPSM | NPSM | Brass Part #    |  |
|------|------|-----------------|--|
| 1/8" | 1/8" | <b>176-0202</b> |  |
| 1/4" | 1/4" | <b>176-0404</b> |  |
| 3/8" | 3/8" | <b>176-0606</b> |  |
| 1/2" | 1/2" | <b>176-0808</b> |  |



## female NPSH x female NPSH swivel

| Female NPSH | Female NPSH | Brass Part #  |  |
|-------------|-------------|---------------|--|
| 1"          | 1"          | <b>BA1616</b> |  |



## female hex couplings

• ref SAE 130138

| NPTF Thread | Brass Part #  |  |  |
|-------------|---------------|--|--|
| 1/8" x 1/8" | <b>BA1F1F</b> |  |  |
| 1/4" x 1/4" | <b>BA2F2F</b> |  |  |
| 3/8" x 3/8" | <b>BA3F3F</b> |  |  |
| 1/2" x 1/2" | <b>BA4F4F</b> |  |  |
| 3/4" x 3/4" | <b>BA6F6F</b> |  |  |



## hex socket plugs

| NPT Thread | Brass Part #    |  | Opt Qty |
|------------|-----------------|--|---------|
| 1/8"       | <b>219-0200</b> |  | 50      |
| 1/4"       | <b>219-0400</b> |  | 100     |
| 3/8"       | <b>219-0600</b> |  | 25      |
| 1/2"       | <b>219-0800</b> |  | 25      |
| 3/4"       | <b>219-1200</b> |  | 25      |



## threaded unions

| NPT Thread | Brass Part # |  |  |
|------------|--------------|--|--|
| 1/4"       | <b>TUN2F</b> |  |  |
| 3/8"       | <b>TUN3F</b> |  |  |
| 1/2"       | <b>TUN4F</b> |  |  |



## ball seat to male pipe

| NPSM | NPTF | Brass Part # |  | Opt Qty |
|------|------|--------------|--|---------|
| 1/8" | 1/8" | <b>BSM11</b> |  | 100     |
| 1/4" | 1/8" | <b>BSM21</b> |  | 100     |
| 1/4" | 1/4" | <b>BSM22</b> |  | 100     |
| 3/8" | 1/4" | <b>BSM32</b> |  | 100     |
| 3/8" | 3/8" | <b>BSM33</b> |  | 50      |
| 3/8" | 1/2" | <b>BSM34</b> |  | 50      |
| 1/2" | 3/8" | <b>BSM43</b> |  | 50      |
| 1/2" | 1/2" | <b>BSM44</b> |  | 50      |
| 3/4" | 3/4" | <b>BSM66</b> |  | 25      |



## Bulkhead Couplings

| Brass Part #   | Female NPTF | Hole Size | Length |  |
|----------------|-------------|-----------|--------|--|
| <b>207BH2</b>  | 1/8"        | 5/8"      | 1.50"  |  |
| <b>207BH4</b>  | 1/4"        | 3/4"      | 1.50"  |  |
| <b>207BH4S</b> | 1/4"        | 3/4"      | .94"   |  |
| <b>207BH6</b>  | 3/8"        | 1"        | 1.31"  |  |
| <b>207BH8</b>  | 1/2"        | 1-1/8"    | 1.50"  |  |
| <b>207BH12</b> | 3/4"        | 1-5/16"   | 1.50"  |  |



## Adapters

## reducer hex bushings

- ref SAE 130140



| Female NPTF | Male NPTF | Brass Part #  |  | Opt Qty |
|-------------|-----------|---------------|--|---------|
| 1/8"        | 1/4"      | <b>HB1F2M</b> |  | 100     |
| 1/8"        | 3/8"      | <b>HB1F3M</b> |  | 100     |
| 1/8"        | 1/2"      | <b>HB1F4M</b> |  | 25      |
| 1/8"        | 3/4"      | <b>HB1F6M</b> |  | 25      |
| 1/4"        | 3/8"      | <b>HB2F3M</b> |  | 100     |
| 1/4"        | 1/2"      | <b>HB2F4M</b> |  | 50      |
| 1/4"        | 3/4"      | <b>HB2F6M</b> |  | 25      |
| 1/4"        | 1"        | <b>HB2F8M</b> |  | 10      |
| 3/8"        | 1/2"      | <b>HB3F4M</b> |  | 50      |
| 3/8"        | 3/4"      | <b>HB3F6M</b> |  | 25      |
| 3/8"        | 1"        | <b>HB3F8M</b> |  | 10      |
| 1/2"        | 3/4"      | <b>HB4F6M</b> |  | 25      |
| 1/2"        | 1"        | <b>HB4F8M</b> |  | 10      |
| 3/4"        | 1"        | <b>HB6F8M</b> |  | 10      |

## reducer hex nipples

- ref SAE 130137



| NPTF Thread | Brass Part #  |  | Opt Qty |
|-------------|---------------|--|---------|
| 1/4" x 1/8" | <b>HN2M1M</b> |  | 100     |
| 3/8" x 1/8" | <b>HN3M1M</b> |  | 50      |
| 3/8" x 1/4" | <b>HN3M2M</b> |  | 50      |
| 1/2" x 1/4" | <b>HN4M2M</b> |  | 50      |
| 1/2" x 3/8" | <b>HN4M3M</b> |  | 50      |
| 3/4" x 1/2" | <b>HN6M4M</b> |  | 25      |

## threaded adapters



| Female NPTF | Male NPSM | Brass Part #    |  | Opt Qty |
|-------------|-----------|-----------------|--|---------|
| 1/4"        | 1/4"      | <b>174-0404</b> |  | 100     |
| 3/8"        | 3/8"      | <b>174-0606</b> |  | 50      |
| 1/2"        | 1/2"      | <b>174-0808</b> |  | 50      |



| Female NPTF | Male NPTF | Brass Part #  |  | Opt Qty |
|-------------|-----------|---------------|--|---------|
| 1/8"        | 1/8"      | <b>RA1F1M</b> |  | 100     |
| 1/4"        | 1/4"      | <b>RA2F2M</b> |  | 50      |
| 3/8"        | 3/8"      | <b>RA3F3M</b> |  | 50      |
| 1/2"        | 1/2"      | <b>RA4F4M</b> |  | 25      |
| 3/4"        | 3/4"      | <b>RA6F6M</b> |  | 10      |

## reducer adapters

- ref SAE 130139



| Female NPTF | Male NPTF | Brass Part #  |  | Opt Qty |
|-------------|-----------|---------------|--|---------|
| 1/4"        | 1/8"      | <b>RA2F1M</b> |  | 50      |
| 3/8"        | 1/8"      | <b>RA3F1M</b> |  | 50      |
| 3/8"        | 1/4"      | <b>RA3F2M</b> |  | 50      |
| 1/2"        | 1/4"      | <b>RA4F2M</b> |  | 25      |
| 1/2"        | 3/8"      | <b>RA4F3M</b> |  | 25      |
| 3/4"        | 3/8"      | <b>RA6F3M</b> |  | 10      |
| 3/4"        | 1/2"      | <b>RA6F4M</b> |  | 10      |

## reducer couplings

- ref SAE 130138



| NPTF Thread | Brass Part #  |  |
|-------------|---------------|--|
| 1/4" x 1/8" | <b>RC2F1F</b> |  |
| 3/8" x 1/8" | <b>RC3F1F</b> |  |
| 3/8" x 1/4" | <b>RC3F2F</b> |  |
| 1/2" x 1/4" | <b>RC4F2F</b> |  |
| 1/2" x 3/8" | <b>RC4F3F</b> |  |
| 3/4" x 3/8" | <b>RC6F3F</b> |  |
| 3/4" x 1/2" | <b>RC6F4F</b> |  |

## NPT pipe caps



| NPT Thread | Brass Part #    |  | Opt Qty |
|------------|-----------------|--|---------|
| 1/8"       | <b>213-0200</b> |  | 50      |
| 1/4"       | <b>213-0400</b> |  | 100     |
| 3/8"       | <b>213-0600</b> |  | 25      |
| 1/2"       | <b>213-0800</b> |  | 25      |
| 3/4"       | <b>213-1200</b> |  | 25      |

## Pipe Nipples

## long pipe nipples

| NPT Thread | Length | Brass Part #    | Opt Qty |
|------------|--------|-----------------|---------|
| 1/8"       | 1-1/2" | <b>166-0215</b> | 25      |
| 1/8"       | 2"     | <b>166-0220</b> | 25      |
| 1/8"       | 2-1/2" | <b>166-0225</b> | 25      |
| 1/8"       | 3"     | <b>166-0230</b> | 25      |
| 1/8"       | 3-1/2" | <b>166-0235</b> | 10      |
| 1/8"       | 4"     | <b>166-0240</b> | 10      |
| 1/4"       | 1-1/2" | <b>166-0415</b> | 25      |
| 1/4"       | 2"     | <b>166-0420</b> | 25      |
| 1/4"       | 2-1/2" | <b>166-0425</b> | 25      |
| 1/4"       | 3"     | <b>166-0430</b> | 25      |
| 1/4"       | 3-1/2" | <b>166-0435</b> | 10      |
| 1/4"       | 4"     | <b>166-0440</b> | 10      |
| 1/4"       | 5"     | <b>166-0450</b> | 5       |
| 3/8"       | 1-1/2" | <b>166-0615</b> | 25      |
| 3/8"       | 2"     | <b>166-0620</b> | 25      |
| 3/8"       | 2-1/2" | <b>166-0625</b> | 10      |
| 3/8"       | 3"     | <b>166-0630</b> | 10      |
| 3/8"       | 3-1/2" | <b>166-0635</b> | 10      |
| 3/8"       | 4"     | <b>166-0640</b> | 5       |
| 1/2"       | 1-1/2" | <b>166-0815</b> | 10      |
| 1/2"       | 2"     | <b>166-0820</b> | 10      |
| 1/2"       | 2-1/2" | <b>166-0825</b> | 10      |
| 1/2"       | 3"     | <b>166-0830</b> | 10      |
| 1/2"       | 3-1/2" | <b>166-0835</b> | 10      |
| 1/2"       | 4"     | <b>166-0840</b> | 5       |
| 3/4"       | 2"     | <b>166-1220</b> | 25      |
| 3/4"       | 2-1/2" | <b>166-1225</b> | 25      |
| 3/4"       | 3"     | <b>166-1230</b> | 25      |
| 3/4"       | 3-1/2" | <b>166-1235</b> | 25      |
| 1"         | 2"     | <b>TN100X2B</b> | ---     |
| 1"         | 3"     | <b>TN100X3B</b> | ---     |
| 1"         | 4"     | <b>TN100X4B</b> | ---     |
| 1 1/2"     | 2"     | <b>TN150X2B</b> | ---     |
| 1 1/2"     | 3"     | <b>TN150X3B</b> | ---     |
| 2"         | 3"     | <b>TN200X3B</b> | ---     |
| 2"         | 4"     | <b>TN200X4B</b> | ---     |
| 2"         | 6"     | <b>TN200X6B</b> | ---     |

- carbon steel and stainless steel nipples are available on page 629



## close pipe nipples

| NPT Thread | Brass Part #    | Opt Qty |
|------------|-----------------|---------|
| 1/8"       | <b>165-0202</b> | 50      |
| 1/4"       | <b>165-0404</b> | 50      |
| 3/8"       | <b>165-0606</b> | 100     |
| 1/2"       | <b>165-0808</b> | 25      |
| 3/4"       | <b>165-1212</b> | 25      |
| 1"         | <b>165-1616</b> | 25      |
| 1 1/2"     | <b>CN150B</b>   | 5       |
| 2"         | <b>CN200B</b>   | 5       |
| 3"         | <b>CN300B</b>   | 5       |

- carbon steel, galvanized steel and stainless steel nipples are available on pages 239 and 628



## Pipe Crosses - Extruded

| Female NPTF Size | Brass Part #    | Opt Qty |
|------------------|-----------------|---------|
| 1/8"             | <b>228-0202</b> | 25      |
| 1/4"             | <b>228-0404</b> | 25      |
| 3/8"             | <b>228-0606</b> | 25      |
| 1/2"             | <b>228-0808</b> | 10      |
| 3/4"             | <b>228-1212</b> | 10      |





## Tees

### street tees - extruded



• ref SAE 130424

| Female NPTF | Male NPTF | Brass Part #    | Opt Qty |
|-------------|-----------|-----------------|---------|
| 1/8"        | 1/8"      | <b>326-0202</b> | 25      |
| 1/4"        | 1/4"      | <b>326-0404</b> | 25      |
| 3/8"        | 3/8"      | <b>326-0606</b> | 25      |
| 1/2"        | 1/2"      | <b>326-0808</b> | 25      |
| 3/4"        | 3/4"      | <b>326-1212</b> | 10      |

### male branch tees - extruded



• ref SAE 130425

| NPTF Thread | Brass Part #    | Opt Qty |
|-------------|-----------------|---------|
| 1/8"        | <b>324-0202</b> | 25      |
| 1/4"        | <b>324-0404</b> | 25      |
| 3/8"        | <b>324-0606</b> | 25      |
| 1/2"        | <b>324-0808</b> | 25      |
| 3/4"        | <b>324-1212</b> | 10      |

### female tees - extruded



• ref SAE 130438

| NPTF Thread | Brass Part #    | Opt Qty |
|-------------|-----------------|---------|
| 1/8"        | <b>322-0202</b> | 25      |
| 1/4"        | <b>322-0404</b> | 25      |
| 3/8"        | <b>322-0606</b> | 25      |
| 1/2"        | <b>322-0808</b> | 25      |
| 3/4"        | <b>322-1212</b> | 10      |

## Elbows

### 90° male pipe elbows - forged



| Male PTF | Brass Part #    | Opt Qty |
|----------|-----------------|---------|
| 1/8"     | <b>169-0202</b> | 25      |
| 1/4"     | <b>169-0404</b> | 25      |
| 3/8"     | <b>169-0606</b> | 25      |
| 1/2"     | <b>169-0808</b> | 25      |

### 90° female pipe elbows - extruded



• ref SAE 130238

| Female NPTF | Brass Part #  | Opt Qty |
|-------------|---------------|---------|
| 1/8"        | <b>EL1F1F</b> | 25      |
| 1/4"        | <b>EL2F2F</b> | 25      |
| 3/8"        | <b>EL3F3F</b> | 25      |
| 1/2"        | <b>EL4F4F</b> | 25      |
| 3/4"        | <b>EL6F6F</b> | 10      |

### 90° street elbows - extruded



• ref SAE 130239

| Female NPTF | Male NPTF | Brass Part #  | Opt Qty |
|-------------|-----------|---------------|---------|
| 1/8"        | 1/8"      | <b>SE1F1M</b> | 25      |
| 1/4"        | 1/8"      | <b>SE2F1M</b> | 25      |
| 1/4"        | 1/4"      | <b>SE2F2M</b> | 25      |
| 3/8"        | 1/4"      | <b>SE3F2M</b> | 25      |
| 3/8"        | 3/8"      | <b>SE3F3M</b> | 25      |
| 1/2"        | 3/8"      | <b>SE4F3M</b> | 25      |
| 1/2"        | 1/2"      | <b>SE4F4M</b> | 25      |
| 3/4"        | 1/2"      | <b>SE6F4M</b> | 25      |
| 3/4"        | 3/4"      | <b>SE6F6M</b> | 10      |

### 45° street elbows - extruded



• ref SAE 130339

| Female NPTF | Male NPTF | Brass Part #    | Opt Qty |
|-------------|-----------|-----------------|---------|
| 1/8"        | 1/8"      | <b>306-0202</b> | 25      |
| 1/4"        | 1/4"      | <b>306-0404</b> | 25      |
| 3/8"        | 3/8"      | <b>306-0606</b> | 25      |
| 1/2"        | 1/2"      | <b>306-0808</b> | 25      |
| 3/4"        | 3/4"      | <b>306-1212</b> | 10      |

# Barbed Hose Fittings

## male inserts

| Hose ID | NPTF Thread | Brass Part # | Opt Qty | Hose ID | NPTF Thread | Brass Part # | Opt Qty |
|---------|-------------|--------------|---------|---------|-------------|--------------|---------|
| 1/8"    | 1/8"        | <b>BN11</b>  | 100     | 1/2"    | 1/4"        | <b>BN42</b>  | 50      |
| 1/8"    | 1/4"        | <b>BN122</b> | 100     | 1/2"    | 3/8"        | <b>BN43</b>  | 50      |
| 3/16"   | 1/8"        | <b>BN151</b> | 100     | 1/2"    | 1/2"        | <b>BN44</b>  | 50      |
| 3/16"   | 1/4"        | <b>BN152</b> | 100     | 1/2"    | 3/4"        | <b>BN46</b>  | 25      |
| 1/4"    | 1/8"        | <b>BN21</b>  | 100     | 5/8"    | 3/8"        | <b>BN53</b>  | 50      |
| 1/4"    | 1/4"        | <b>BN22</b>  | 100     | 5/8"    | 1/2"        | <b>BN54</b>  | 25      |
| 1/4"    | 3/8"        | <b>BN23</b>  | 100     | 5/8"    | 3/4"        | <b>BN56</b>  | 50      |
| 1/4"    | 1/2"        | <b>BN24</b>  | 50      | 3/4"    | 1/2"        | <b>BN64</b>  | 50      |
| 5/16"   | 1/8"        | <b>BN251</b> | 100     | 3/4"    | 3/4"        | <b>BN66</b>  | 25      |
| 5/16"   | 1/4"        | <b>BN252</b> | 50      | 1"      | 3/4"        | <b>BN86</b>  | 25      |
| 5/16"   | 3/8"        | <b>BN253</b> | 50      | 1"      | 1"          | <b>BN88</b>  | 10      |
| 3/8"    | 1/8"        | <b>BN31</b>  | 100     | 1-1/4"  | 3/4"        | <b>BN106</b> | 10      |
| 3/8"    | 1/4"        | <b>BN32</b>  | 100     | 1-1/4"  | 1"          | <b>BN108</b> | 10      |
| 3/8"    | 3/8"        | <b>BN33</b>  | 50      |         |             |              |         |
| 3/8"    | 1/2"        | <b>BN34</b>  | 25      |         |             |              |         |
| 3/8"    | 3/4"        | <b>BN36</b>  | 25      |         |             |              |         |

## BSPT male inserts

| Hose ID | BSPT Thread | Brass Part #    | Opt Qty |
|---------|-------------|-----------------|---------|
| 1/4"    | 1/8"        | <b>BN21BSPT</b> | 100     |
| 1/4"    | 1/4"        | <b>BN22BSPT</b> | 100     |
| 3/8"    | 1/4"        | <b>BN32BSPT</b> | 100     |
| 3/8"    | 3/8"        | <b>BN33BSPT</b> | 50      |
| 3/8"    | 1/2"        | <b>BN34BSPT</b> | 25      |
| 1/2"    | 3/8"        | <b>BN43BSPT</b> | 50      |
| 1/2"    | 1/2"        | <b>BN44BSPT</b> | 50      |
| 3/4"    | 3/4"        | <b>BN66BSPT</b> | 25      |
| 1"      | 1"          | <b>BN88BSPT</b> | 10      |

## solid female inserts

| Hose ID | NPTF Thread | Brass Part # | 303 Stainless Part # | Opt Qty |
|---------|-------------|--------------|----------------------|---------|
| 1/8"    | 1/8"        | <b>BF11</b>  | ---                  | 100     |
| 1/8"    | 1/4"        | <b>BF12</b>  | ---                  | 100     |
| 3/16"   | 1/8"        | <b>BF151</b> | ---                  | 100     |
| 3/16"   | 1/4"        | <b>BF152</b> | ---                  | 100     |
| 1/4"    | 1/8"        | <b>BF21</b>  | ---                  | 100     |
| 1/4"    | 1/4"        | <b>BF22</b>  | <b>BF22SS</b>        | 100     |
| 1/4"    | 3/8"        | <b>BF23</b>  | ---                  | 50      |
| 1/4"    | 1/2"        | <b>BF24</b>  | ---                  | 50      |
| 5/16"   | 1/8"        | <b>BF251</b> | ---                  | 100     |
| 5/16"   | 1/4"        | <b>BF252</b> | ---                  | 100     |
| 5/16"   | 3/8"        | <b>BF253</b> | ---                  | 100     |
| 3/8"    | 1/8"        | <b>BF31</b>  | ---                  | 100     |
| 3/8"    | 1/4"        | <b>BF32</b>  | <b>BF32SS</b>        | 50      |
| 3/8"    | 3/8"        | <b>BF33</b>  | <b>BF33SS</b>        | 50      |
| 3/8"    | 1/2"        | <b>BF34</b>  | ---                  | 50      |
| 3/8"    | 3/4"        | <b>BF36</b>  | ---                  | 25      |
| 1/2"    | 1/4"        | <b>BF42</b>  | ---                  | 50      |
| 1/2"    | 3/8"        | <b>BF43</b>  | ---                  | 50      |
| 1/2"    | 1/2"        | <b>BF44</b>  | <b>BF44SS</b>        | 50      |
| 1/2"    | 3/4"        | <b>BF46</b>  | ---                  | 25      |
| 5/8"    | 3/8"        | <b>BF53</b>  | ---                  | 50      |
| 5/8"    | 1/2"        | <b>BF54</b>  | ---                  | 25      |
| 5/8"    | 3/4"        | <b>BF56</b>  | ---                  | 25      |
| 3/4"    | 1/2"        | <b>BF64</b>  | ---                  | 25      |
| 3/4"    | 3/4"        | <b>BF66</b>  | ---                  | 20      |
| 1"      | 3/4"        | <b>BF86</b>  | ---                  | 20      |
| 1"      | 1"          | <b>BF88</b>  | ---                  | 10      |
| 1-1/4"  | 1"          | <b>BF108</b> | ---                  | 10      |





## Beaded Hose Barbs



| Hose ID | Male NPTF Thread | Brass Part #    |  | Pkg Qty |
|---------|------------------|-----------------|--|---------|
| 1/4"    | 1/8"             | <b>268B0402</b> |  | 100     |
| 1/4"    | 1/4"             | <b>268B0404</b> |  | 100     |
| 5/16"   | 1/8"             | <b>268B0502</b> |  | 100     |
| 5/16"   | 1/4"             | <b>268B0504</b> |  | 50      |
| 3/8"    | 1/8"             | <b>268B0602</b> |  | 100     |
| 3/8"    | 1/4"             | <b>268B0604</b> |  | 100     |
| 3/8"    | 3/8"             | <b>268B0606</b> |  | 50      |
| 1/2"    | 3/8"             | <b>268B0806</b> |  | 50      |
| 1/2"    | 1/2"             | <b>268B0808</b> |  | 50      |
| 5/8"    | 1/2"             | <b>268B1008</b> |  | 25      |
| 3/4"    | 1/2"             | <b>268B1208</b> |  | 50      |
| 3/4"    | 3/4"             | <b>268B1212</b> |  | 25      |

## Barbed Hose Elbows

**male insert 45° elbows - forged**



| Hose ID | NPTF Thread | Brass Part #    |  | Pkg Qty |
|---------|-------------|-----------------|--|---------|
| 1/4"    | 1/8"        | <b>139-0402</b> |  | 100     |
| 1/4"    | 1/4"        | <b>139-0404</b> |  | 25      |
| 3/8"    | 1/8"        | <b>139-0602</b> |  | 100     |
| 3/8"    | 1/4"        | <b>139-0604</b> |  | 100     |
| 3/8"    | 3/8"        | <b>139-0606</b> |  | 25      |
| 1/2"    | 1/4"        | <b>139-0804</b> |  | 25      |
| 1/2"    | 3/8"        | <b>139-0806</b> |  | 25      |
| 1/2"    | 1/2"        | <b>139-0808</b> |  | 25      |
| 3/4"    | 1/2"        | <b>139-1208</b> |  | 25      |

**female insert 90° elbows - forged**



| Hose ID | NPTF Thread | Brass Part #    |  | Pkg Qty |
|---------|-------------|-----------------|--|---------|
| 1/4"    | 1/8"        | <b>134-0402</b> |  | 50      |
| 1/4"    | 1/4"        | <b>134-0404</b> |  | 50      |
| 3/8"    | 1/4"        | <b>134-0604</b> |  | 50      |
| 3/8"    | 3/8"        | <b>134-0606</b> |  | 50      |
| 1/2"    | 1/4"        | <b>134-0804</b> |  | 25      |
| 1/2"    | 3/8"        | <b>134-0806</b> |  | 25      |
| 1/2"    | 1/2"        | <b>134-0808</b> |  | 25      |
| 3/4"    | 3/4"        | <b>134-1212</b> |  | 25      |

## Barbed Hose Elbows

male insert 90° elbows - forged

| Hose ID | NPTF Thread | Brass Part #   |  | 316 Stainless <sup>1</sup> Part # |     | Opt Qty |
|---------|-------------|----------------|--|-----------------------------------|-----|---------|
| 3/16"   | 1/8"        | <b>EL15H1M</b> |  | ---                               | --- | 50      |
| 1/4"    | 1/8"        | <b>EL2H1M</b>  |  | ---                               | --- | 50      |
| 1/4"    | 1/4"        | <b>EL2H2M</b>  |  | <b>EL2H2MSS</b>                   |     | 50      |
| 1/4"    | 3/8"        | <b>EL2H3M</b>  |  | ---                               | --- | 50      |
| 5/16"   | 1/8"        | <b>EL25H1M</b> |  | ---                               | --- | 25      |
| 5/16"   | 1/4"        | <b>EL25H2M</b> |  | ---                               | --- | 50      |
| 5/16"   | 3/8"        | <b>EL25H3M</b> |  | ---                               | --- | 50      |
| 3/8"    | 1/8"        | <b>EL3H1M</b>  |  | ---                               | --- | 50      |
| 3/8"    | 1/4"        | <b>EL3H2M</b>  |  | <b>EL3H2MSS</b>                   |     | 50      |
| 3/8"    | 3/8"        | <b>EL3H3M</b>  |  | <b>EL3H3MSS</b>                   |     | 50      |
| 3/8"    | 1/2"        | <b>EL3H4M</b>  |  | ---                               | --- | 25      |
| 1/2"    | 1/4"        | <b>EL4H2M</b>  |  | ---                               | --- | 50      |
| 1/2"    | 3/8"        | <b>EL4H3M</b>  |  | ---                               | --- | 50      |
| 1/2"    | 1/2"        | <b>EL4H4M</b>  |  | <b>EL4H4MSS</b>                   |     | 25      |
| 5/8"    | 3/8"        | <b>EL5H3M</b>  |  | ---                               | --- | 25      |
| 5/8"    | 1/2"        | <b>EL5H4M</b>  |  | ---                               | --- | 25      |
| 3/4"    | 1/2"        | <b>EL6H4M</b>  |  | ---                               | --- | 25      |
| 3/4"    | 3/4"        | <b>EL6H6M</b>  |  | <b>EL6H6MSS</b>                   |     | 25      |
| 1"      | 3/4"        | <b>EL8H6M</b>  |  | ---                               | --- | 10      |
| 1"      | 1"          | <b>EL8H8M</b>  |  | ---                               | --- | 10      |

<sup>1</sup> 316 stainless steel parts have NPT threads



## Barbed Hose Splicers

hose barb 90° elbow splicers - forged

| Hose ID     | Brass Part #    |  | 304 Stainless <sup>NEW</sup> Part # |     | Pkg Qty |
|-------------|-----------------|--|-------------------------------------|-----|---------|
| 1/8"        | <b>177-0202</b> |  | <b>177-0202SS</b>                   |     | 25      |
| 3/16"       | <b>177-0303</b> |  | <b>177-0303SS</b>                   |     | 25      |
| 1/4" x 1/8" | <b>177-0402</b> |  | ---                                 | --- | 25      |
| 1/4"        | <b>177-0404</b> |  | <b>177-0404SS</b>                   |     | 25      |
| 5/16"       | <b>177-0505</b> |  | ---                                 | --- | 25      |
| 3/8" x 1/4" | <b>177-0604</b> |  | ---                                 | --- | 25      |
| 3/8"        | <b>177-0606</b> |  | <b>177-0606SS</b>                   |     | 25      |
| 1/2" x 3/8" | <b>177-0806</b> |  | ---                                 | --- | 25      |
| 1/2"        | <b>177-0808</b> |  | <b>177-0808SS</b>                   |     | 25      |
| 5/8"        | <b>177-1010</b> |  | ---                                 | --- | 25      |
| 3/4" x 1/2" | <b>177-1208</b> |  | ---                                 | --- | 25      |
| 3/4"        | <b>177-1212</b> |  | ---                                 | --- | 25      |



hose barb tee splicers - forged

| Hose ID     | Brass Part #                |  | 304 Stainless <sup>NEW</sup> Part # |     | Pkg Qty |
|-------------|-----------------------------|--|-------------------------------------|-----|---------|
| 1/8"        | <b>179-0202</b>             |  | <b>179-0202SS</b>                   |     | 25      |
| 3/16"       | <b>179-0303</b>             |  | <b>179-0303SS</b>                   |     | 100     |
| 1/4" x 1/8" | <b>179-0402</b>             |  | ---                                 | --- | 25      |
| 1/4"        | <b>179-0404</b>             |  | <b>179-0404SS</b>                   |     | 25      |
| 5/16"       | <b>179-0505</b>             |  | ---                                 | --- | 25      |
| 3/8" x 1/4" | <b>179-0604<sup>1</sup></b> |  | ---                                 | --- | 25      |
| 3/8"        | <b>179-0606</b>             |  | <b>179-0606SS</b>                   |     | 25      |
| 1/2" x 3/8" | <b>179-0806</b>             |  | ---                                 | --- | 25      |
| 1/2"        | <b>179-0808</b>             |  | <b>179-0808SS</b>                   |     | 25      |
| 5/8"        | <b>179-1010</b>             |  | ---                                 | --- | 25      |
| 3/4" x 1/2" | <b>179-1208</b>             |  | ---                                 | --- | 25      |
| 3/4"        | <b>179-1212</b>             |  | ---                                 | --- | 20      |



<sup>1</sup> drop leg has 1/4-18 male NPTF thread

## Hose Menders



| Hose ID     | Brass Part # |  | Pkg Qty |
|-------------|--------------|--|---------|
| 1/8"        | <b>BM1</b>   |  | 100     |
| 3/16"       | <b>BM15</b>  |  | 100     |
| 1/4"        | <b>BM2</b>   |  | 100     |
| 1/4" x 1/8" | <b>BM2-1</b> |  | 100     |
| 5/16"       | <b>BM25</b>  |  | 100     |
| 3/8"        | <b>BM3</b>   |  | 100     |
| 3/8" x 1/4" | <b>BM3-2</b> |  | 100     |
| 1/2"        | <b>BM4</b>   |  | 50      |
| 1/2" x 3/8" | <b>BM4-3</b> |  | 50      |
| 5/8"        | <b>BM5</b>   |  | 50      |
| 5/8" x 3/8" | <b>BM5-3</b> |  | 50      |
| 5/8" x 1/2" | <b>BM5-4</b> |  | 50      |
| 3/4"        | <b>BM6</b>   |  | 50      |
| 3/4" x 1/2" | <b>BM6-4</b> |  | 50      |
| 1"          | <b>BM8</b>   |  | 10      |

## Barbed Hose Fittings

## male 45° SAE x hose barb



| Hose ID | UNF Thread | Brass Part #    |  | Pkg Qty |
|---------|------------|-----------------|--|---------|
| 3/16"   | 7/16"-20   | <b>142-0307</b> |  | 100     |
| 1/4"    | 7/16"-20   | <b>142-0407</b> |  | 100     |
| 1/4"    | 5/8"-18    | <b>142-0410</b> |  | 100     |
| 5/16"   | 1/2"-20    | <b>142-0508</b> |  | 100     |
| 3/8"    | 5/8"-18    | <b>142-0610</b> |  | 50      |
| 3/8"    | 3/4"-16    | <b>142-0612</b> |  | 50      |
| 1/2"    | 3/4"-16    | <b>142-0812</b> |  | 50      |

## male NPTF swivel x hose barb



| Hose ID | NPTF Size | Brass Part #                 |  | Pkg Qty |
|---------|-----------|------------------------------|--|---------|
| 1/4"    | 1/8"      | <b>103-0402</b>              |  | 100     |
| 1/4"    | 1/4"      | <b>103-0404</b>              |  | 100     |
| 3/8"    | 1/4"      | <b>103-0604</b>              |  | 100     |
| 3/8"    | 3/8"      | <b>103-0606</b>              |  | 50      |
| 1/2"    | 3/8"      | <b>103-0806</b>              |  | 50      |
| 1/2"    | 1/2"      | <b>103-0808</b>              |  | 25      |
| 3/4"    | 3/4"      | <b>103-1212</b>              |  | 25      |
| 1"      | 1-11½"    | <b>103-1616</b> <sup>1</sup> |  | 10      |

Note: swivel is for assembly convenience only, not for live swivel applications.

<sup>1</sup> capped threads / 150 maximum PSI

## female NPTF swivel x hose barb



| Hose ID | NPTF Thread | Brass Part #    |  | Pkg Qty |
|---------|-------------|-----------------|--|---------|
| 1/4"    | 1/4"        | <b>105-0404</b> |  | 100     |
| 3/8"    | 1/4"        | <b>105-0604</b> |  | 50      |
| 3/8"    | 3/8"        | <b>105-0606</b> |  | 50      |
| 1/2"    | 3/8"        | <b>105-0806</b> |  | 50      |
| 1/2"    | 1/2"        | <b>105-0808</b> |  | 50      |

Note: swivel is for assembly convenience only, not for live swivel applications.

## female 37° JIC swivel x hose barb



| Hose ID | UNF Thread | Brass Part #    |  | Pkg Qty |
|---------|------------|-----------------|--|---------|
| 3/8"    | 9/16"-18   | <b>145-0609</b> |  | 100     |
| 3/4"    | 1-1/16"-12 | <b>145-1217</b> |  | 25      |

## Barbed Hose Fittings

### female NPSM swivel x hose barb ball seat type

| Hose ID | NPSM Thread | Brass Part #  |  | Pkg Qty |
|---------|-------------|---------------|--|---------|
| 1/8"    | 1/8"        | <b>BFS11</b>  |  | 100     |
| 3/16"   | 1/8"        | <b>BFS151</b> |  | 100     |
| 3/16"   | 1/4"        | <b>BFS152</b> |  | 100     |
| 1/4"    | 1/8"        | <b>BFS21</b>  |  | 100     |
| 1/4"    | 1/4"        | <b>BFS22</b>  |  | 100     |
| 1/4"    | 3/8"        | <b>BFS23</b>  |  | 100     |
| 5/16"   | 1/4"        | <b>BFS252</b> |  | 100     |
| 5/16"   | 3/8"        | <b>BFS253</b> |  | 50      |
| 3/8"    | 1/4"        | <b>BFS32</b>  |  | 100     |
| 3/8"    | 3/8"        | <b>BFS33</b>  |  | 100     |
| 3/8"    | 1/2"        | <b>BFS34</b>  |  | 100     |
| 1/2"    | 3/8"        | <b>BFS43</b>  |  | 50      |
| 1/2"    | 1/2"        | <b>BFS44</b>  |  | 100     |
| 3/4"    | 3/4"        | <b>BFS66</b>  |  | 50      |



### female NPSM swivel x hose barb gasket seat type

| Hose ID | NPSM Thread | Brass Part #    |  | Pkg Qty |
|---------|-------------|-----------------|--|---------|
| 1/8"    | 1/8"        | <b>126-0202</b> |  | 100     |
| 3/16"   | 1/8"        | <b>126-0302</b> |  | 100     |
| 3/16"   | 1/4"        | <b>126-0304</b> |  | 100     |
| 1/4"    | 1/8"        | <b>126-0402</b> |  | 100     |
| 1/4"    | 1/4"        | <b>126-0404</b> |  | 100     |
| 1/4"    | 3/8"        | <b>126-0406</b> |  | 100     |
| 5/16"   | 1/4"        | <b>126-0504</b> |  | 100     |
| 3/8"    | 1/4"        | <b>126-0604</b> |  | 100     |
| 3/8"    | 3/8"        | <b>126-0606</b> |  | 50      |
| 3/8"    | 1/2"        | <b>126-0608</b> |  | 50      |
| 1/2"    | 3/8"        | <b>126-0806</b> |  | 50      |
| 1/2"    | 1/2"        | <b>126-0808</b> |  | 50      |
| 3/4"    | 3/4"        | <b>126-1212</b> |  | 25      |



Note: not recommended for water.

### female 45° SAE swivel x hose barb

| Hose ID | UNF Thread | Brass Part #    |  | Pkg Qty |
|---------|------------|-----------------|--|---------|
| 3/16"   | 3/8"-24    | <b>144-0306</b> |  | 100     |
| 1/4"    | 5/8"-18    | <b>144-0410</b> |  | 100     |
| 5/16"   | 5/8"-18    | <b>144-0510</b> |  | 100     |
| 3/8"    | 5/8"-18    | <b>144-0610</b> |  | 100     |
| 1/2"    | 3/4"-16    | <b>144-0812</b> |  | 100     |
| 3/4"    | 1-1/16"-14 | <b>144-1217</b> |  | 25      |



### female 45°SAE / 37°JIC swivel x hose barb (dual angle seat)

| Hose ID | UNF Thread | Brass Part #    |  | Pkg Qty |
|---------|------------|-----------------|--|---------|
| 3/16"   | 7/16"-20   | <b>143-0307</b> |  | 100     |
| 1/4"    | 7/16"-20   | <b>143-0407</b> |  | 100     |
| 1/4"    | 1/2"-20    | <b>143-0408</b> |  | 100     |
| 5/16"   | 1/2"-20    | <b>143-0508</b> |  | 100     |
| 3/8"    | 3/4"-16    | <b>143-0612</b> |  | 100     |
| 1/2"    | 3/4"-16    | <b>143-0812</b> |  | 100     |
| 1/2"    | 7/8"-14    | <b>143-0814</b> |  | 50      |



## Ferrules

for air

**BFM**  
for medium weight  
air hose



**BFL**  
for light weight  
air hose



| Brass Part #   |  | Pkg Qty | Ferrule ID | Ferrule Length | End Hole Size | Metal Gauge | Std Ind Part # | Ribbed Die* | Plain Die*     |
|----------------|--|---------|------------|----------------|---------------|-------------|----------------|-------------|----------------|
| <b>BFM478</b>  |  | 50      | .478"      | 11/16"         | 21/64"        | .024"       | <b>4750</b>    | <b>R41</b>  | <b>P41/P42</b> |
| <b>BFM500</b>  |  | 50      | .500"      | 1"             | 11/32"        | .024"       | <b>7322</b>    | <b>R40</b>  | <b>P40</b>     |
| <b>BFM525</b>  |  | 50      | .525"      | 1"             | 3/8"          | .024"       | <b>7323</b>    | <b>R39</b>  | <b>P39</b>     |
| <b>BFM531</b>  |  | 50      | .531"      | 1"             | 7/16"         | .024"       | <b>7324</b>    | <b>R39</b>  | <b>P39</b>     |
| <b>BFM562</b>  |  | 50      | .562"      | 1"             | 7/16"         | .024"       | <b>7325</b>    | <b>R37</b>  | <b>P38</b>     |
| <b>BFM593</b>  |  | 50      | .593"      | 1"             | 7/16"         | .024"       | <b>7326</b>    | <b>R36</b>  | <b>P37</b>     |
| <b>BFM625</b>  |  | 50      | .625"      | 1"             | 7/16"         | .024"       | <b>7327</b>    | <b>R35</b>  | <b>P36</b>     |
| <b>BFM656</b>  |  | 50      | .656"      | 1"             | 7/16"         | .024"       | <b>7328</b>    | <b>R34</b>  | <b>P35</b>     |
| <b>BFM687</b>  |  | 50      | .687"      | 1"             | 1/2"          | .024"       | <b>7329</b>    | <b>R33</b>  | <b>P34</b>     |
| <b>BFM718</b>  |  | 50      | .718"      | 1"             | 5/8"          | .024"       | <b>7330</b>    | <b>R31</b>  | <b>P32</b>     |
| <b>BFM718B</b> |  | 50      | .718"      | 1"             | 1/2"          | .024"       | <b>7330B</b>   | <b>R31</b>  | <b>P32</b>     |
| <b>BFM750</b>  |  | 50      | .750"      | 1"             | 5/8"          | .024"       | <b>7331</b>    | <b>R30</b>  | <b>P31</b>     |
| <b>BFM750B</b> |  | 50      | .750"      | 1"             | 1/2"          | .024"       | <b>7331B</b>   | <b>R30</b>  | <b>P31</b>     |
| <b>BFM781</b>  |  | 50      | .781"      | 1"             | 5/8"          | .024"       | <b>7332</b>    | <b>R29</b>  | <b>P30</b>     |
| <b>BFM781B</b> |  | 50      | .781"      | 1"             | 1/2"          | .024"       | <b>7332B</b>   | <b>R29</b>  | <b>P30</b>     |
| <b>BFM812</b>  |  | 50      | .812"      | 1"             | 5/8"          | .024"       | <b>7333</b>    | <b>R28</b>  | <b>P29</b>     |
| <b>BFL380</b>  |  | 50      | .380"      | 1/2"           | 17/64"        | .016"       | <b>622</b>     | <b>R44</b>  | <b>P45</b>     |
| <b>BFL400</b>  |  | 50      | .400"      | 15/32"         | 17/64"        | .020"       | <b>619</b>     | <b>R44</b>  | <b>P44</b>     |
| <b>BFL410</b>  |  | 50      | .410"      | 1/2"           | 17/64"        | .016"       | <b>620</b>     | <b>R43</b>  | <b>P44</b>     |
| <b>BFL450</b>  |  | 50      | .450"      | 9/16"          | 11/32"        | .016"       | <b>769</b>     | <b>R41</b>  | <b>P42</b>     |
| <b>BFL500</b>  |  | 50      | .500"      | 1/2"           | 11/32"        | .016"       | <b>624</b>     | <b>R40</b>  | <b>P41</b>     |
| <b>BFL525</b>  |  | 50      | .525"      | 1/2"           | 11/32"        | .016"       | <b>625</b>     | <b>R39</b>  | <b>P40</b>     |
| <b>BFL548</b>  |  | 50      | .548"      | 31/64"         | 3/8"          | .015"       | <b>626</b>     | <b>R38</b>  | <b>P39</b>     |
| <b>BFL564</b>  |  | 50      | .564"      | 3/4"           | 3/8"          | .019"       | <b>3588</b>    | <b>R37</b>  | <b>P38</b>     |
| <b>BFL575</b>  |  | 50      | .575"      | 31/64"         | 15/32"        | .019"       | <b>KK</b>      | <b>R37</b>  | <b>P38</b>     |
| <b>BFL600</b>  |  | 50      | .600"      | 1/2"           | 1/2"          | .019"       | <b>JJ</b>      | <b>R36</b>  | <b>P37</b>     |
| <b>BFL625</b>  |  | 50      | .625"      | 1/2"           | 1/2"          | .019"       | <b>II</b>      | <b>R35</b>  | <b>P36</b>     |
| <b>BFL650</b>  |  | 50      | .650"      | 1/2"           | 1/2"          | .019"       | <b>HH</b>      | <b>R34</b>  | <b>P35</b>     |
| <b>BFL675</b>  |  | 50      | .675"      | 33/64"         | 1/2"          | .019"       | <b>GG</b>      | <b>R34</b>  | <b>P34</b>     |
| <b>BFL725</b>  |  | 50      | .725"      | 17/32"         | 1/2"          | .019"       | <b>EE</b>      | <b>R31</b>  | <b>P32</b>     |
| <b>BFL750</b>  |  | 50      | .750"      | 17/32"         | 1/2"          | .019"       | <b>DD</b>      | <b>R30</b>  | <b>P32</b>     |
| <b>BFL775</b>  |  | 50      | .775"      | 17/32"         | 1/2"          | .016"       | <b>CC</b>      | <b>R31</b>  | <b>P31</b>     |

\* These dies for use with 5111A and 1765A ferrule machine. Other sizes are available.  
Ribbed Dies and Plain Dies.

for fluid

**BFMW**  
for medium weight  
water hose



| Brass Part #    |  | Pkg Qty | Ferrule ID | Ferrule Length | End Hole Size | Metal Gauge | Std Ind Part # | Ribbed Die* | Plain Die* |
|-----------------|--|---------|------------|----------------|---------------|-------------|----------------|-------------|------------|
| <b>BF800</b>    |  | 25      | .800"      | .844"          | .688"         | .024"       | <b>---</b>     | <b>R28</b>  | <b>P29</b> |
| <b>BF825</b>    |  | 25      | .825"      | .844"          | .688"         | .024"       | <b>---</b>     | <b>R27</b>  | <b>P28</b> |
| <b>BF850</b>    |  | 25      | .850"      | .568"          | .688"         | .019"       | <b>Z</b>       | <b>R26</b>  | <b>P27</b> |
| <b>BFW875</b>   |  | 25      | .875"      | .844"          | .688"         | .024"       | <b>7244A</b>   | <b>R25</b>  | <b>P26</b> |
| <b>BFW900</b>   |  | 25      | .900"      | .844"          | .688"         | .024"       | <b>5029A</b>   | <b>R24</b>  | <b>P25</b> |
| <b>BFW925</b>   |  | 25      | .925"      | .840"          | .690"         | .025"       | <b>7113</b>    | <b>R23</b>  | <b>P24</b> |
| <b>BFW975</b>   |  | 25      | .975"      | .844"          | .688"         | .024"       | <b>5028A</b>   | <b>R21</b>  | <b>P22</b> |
| <b>BFW1025</b>  |  | 25      | 1.025"     | .844"          | .693"         | .024"       | <b>7114A</b>   | <b>R19</b>  | <b>P20</b> |
| <b>BFMW1175</b> |  | 25      | 1.175"     | .844"          | .875"         | .024"       | <b>7088A</b>   | <b>R13</b>  | <b>P14</b> |
| <b>BFMW1050</b> |  | 25      | 1.050"     | .625"          | .750"         | .025"       | <b>3605</b>    | <b>R18</b>  | <b>P19</b> |
| <b>BFMW1100</b> |  | 25      | 1.100"     | .843"          | .812"         | .023"       | <b>5027</b>    | <b>R16</b>  | <b>P17</b> |
| <b>BFMW1150</b> |  | 25      | 1.150"     | .844"          | .880"         | .024"       | <b>7104A</b>   | <b>R15</b>  | <b>P15</b> |
| <b>BFMW1225</b> |  | 25      | 1.225"     | .875"          | .875"         | .025"       | <b>875-K</b>   | <b>R11</b>  | <b>P12</b> |
| <b>BFMW1275</b> |  | 25      | 1.275"     | .875"          | 1.000"        | .025"       | <b>875-1</b>   | <b>R9</b>   | <b>P10</b> |
| <b>BFMW1400</b> |  | 25      | 1.400"     | .687"          | 1.120"        | .020"       | <b>D</b>       | <b>R4</b>   | <b>P5</b>  |
| <b>BFMW1500</b> |  | 25      | 1.500"     | .875"          | 1.120"        | .025"       | <b>1500</b>    | <b>---</b>  | <b>P1</b>  |

\* These dies for use with 5111A and 1765A ferrule machine. Other sizes are available.  
Ribbed Dies and Plain Dies per set

sold in package quantities only

## Hose Crimper

**Features:**

- 855 crimper with 5 dies for 31/64" (0.484") to 45/64" (0.703") OD hose
- 855A crimper with 5 dies for 28/64" (0.437") to 43/64" (0.671") OD hose
- optional dies up to 52/64" OD
- replacement dies
- Hose crimper provides "big tool" crimping advantages at a fraction of the cost.
- rugged, portable and easy to use
- # 855 weight: 10 lbs.
- # 855A weight: 10 lbs.

| Crimper Part # |
|----------------|
| <b>855</b>     |
| <b>855A</b>    |



### Replacement Dies

| Die Bore | Hose OD |       | Die Part #    | Crimper # 855 | Crimper # 855A |
|----------|---------|-------|---------------|---------------|----------------|
|          | From:   | To:   |               |               |                |
| .375"    | .385"   | .406" | <b>856-10</b> | optional      | optional       |
| .437"    | .447"   | .468" | <b>856-7</b>  | optional      | standard       |
| .484"    | .490"   | .520" | <b>856-4</b>  | standard      | standard       |
| .531"    | .540"   | .562" | <b>856-3</b>  | standard      | standard       |
| .578"    | .590"   | .625" | <b>856-2</b>  | standard      | standard       |
| .625"    | .640"   | .671" | <b>856-1</b>  | standard      | standard       |
| .687"    | .690"   | .710" | <b>856-5</b>  | standard      | optional       |
| .750"    | .760"   | .781" | <b>856-8</b>  | optional      | optional       |
| .812"    | .820"   | .843" | <b>856-9</b>  | optional      | optional       |

## Large Hose Crimper

**(Sold without dies)**

**Features:**

- for crimping 1/2" to 1" ID hoses with larger OD's, from 11/16" to 1-1/2"
- crimps standard brass or aluminum ferrules
- order separate dies for each hose diameter
- weight: 10 lbs.

| Crimper Part # |
|----------------|
| <b>860</b>     |

### Dies

| Hose OD/<br>Finished Crimp Dimension | Die Part #    |
|--------------------------------------|---------------|
| 11/16"                               | <b>861-22</b> |
| 23/32"                               | <b>861-23</b> |
| 3/4"                                 | <b>861-24</b> |
| 25/32"                               | <b>861-25</b> |
| 13/16"                               | <b>861-26</b> |
| 27/32"                               | <b>861-27</b> |
| 7/8"                                 | <b>861-28</b> |
| 29/32"                               | <b>861-29</b> |
| 15/16"                               | <b>861-30</b> |
| 31/32"                               | <b>861-31</b> |
| 1"                                   | <b>861-32</b> |
| 1-1/32"                              | <b>861-33</b> |
| 1-1/16"                              | <b>861-34</b> |
| 1-1/8"                               | <b>861-36</b> |
| 1-3/16"                              | <b>861-38</b> |
| 1-1/4"                               | <b>861-40</b> |
| 1-5/16"                              | <b>861-42</b> |
| 1-3/8"                               | <b>861-44</b> |
| 1-7/16"                              | <b>861-46</b> |
| 1-1/2"                               | <b>861-48</b> |





## Brass Push-On Fittings



**Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.** No hose clamps or ferrules are needed. Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

### NPTF Hose Barb Fittings



**male NPTF x push-on hose barb**  
National Pipe Tapered - dryseal

| Hose ID | NPTF Thread | Brass Part # | 303 Stainless Part # | Opt Qty |
|---------|-------------|--------------|----------------------|---------|
| 1/4"    | 1/8"        | <b>BP21</b>  | <b>RPN21</b>         | 100     |
| 1/4"    | 1/4"        | <b>BP22</b>  | <b>RPN22</b>         | 100     |
| 1/4"    | 3/8"        | <b>BP23</b>  | ---                  | 50      |
| 5/16"   | 1/8"        | <b>BP251</b> | ---                  | 100     |
| 5/16"   | 1/4"        | <b>BP252</b> | ---                  | 50      |
| 3/8"    | 1/8"        | <b>BP31</b>  | ---                  | 100     |
| 3/8"    | 1/4"        | <b>BP32</b>  | <b>RPN32</b>         | 50      |
| 3/8"    | 3/8"        | <b>BP33</b>  | <b>RPN33</b>         | 50      |
| 3/8"    | 1/2"        | <b>BP34</b>  | ---                  | 25      |
| 3/8"    | 3/4"        | <b>BP36</b>  | ---                  | 25      |
| 1/2"    | 1/4"        | <b>BP42</b>  | <b>RPN42</b>         | 25      |
| 1/2"    | 3/8"        | <b>BP43</b>  | <b>RPN43</b>         | 25      |
| 1/2"    | 1/2"        | <b>BP44</b>  | <b>RPN44</b>         | 50      |
| 1/2"    | 3/4"        | <b>BP46</b>  | ---                  | 50      |
| 5/8"    | 3/8"        | <b>BP53</b>  | ---                  | 25      |
| 5/8"    | 1/2"        | <b>BP54</b>  | ---                  | 25      |
| 5/8"    | 3/4"        | <b>BP56</b>  | ---                  | 25      |
| 3/4"    | 1/2"        | <b>BP64</b>  | <b>RPN64</b>         | 25      |
| 3/4"    | 3/4"        | <b>BP66</b>  | <b>RPN66</b>         | 25      |
| 1"      | 3/4"        | <b>BP86</b>  | ---                  | 10      |
| 1"      | 1"          | <b>BP88</b>  | <b>RPN88</b>         | 10      |



**female NPTF x push-on hose barb**  
National Pipe Tapered - dryseal

| Hose ID | NPTF Thread | Part #       | Opt Qty |
|---------|-------------|--------------|---------|
| 1/4"    | 1/8"        | <b>BP21</b>  | 100     |
| 1/4"    | 1/4"        | <b>BP22</b>  | 100     |
| 1/4"    | 3/8"        | <b>BP23</b>  | 50      |
| 5/16"   | 1/8"        | <b>BP251</b> | 100     |
| 5/16"   | 1/4"        | <b>BP252</b> | 50      |
| 3/8"    | 1/8"        | <b>BP31</b>  | 50      |
| 3/8"    | 1/4"        | <b>BP32</b>  | 50      |
| 3/8"    | 3/8"        | <b>BP33</b>  | 50      |
| 3/8"    | 1/2"        | <b>BP34</b>  | 50      |
| 3/8"    | 3/4"        | <b>BP36</b>  | 25      |
| 1/2"    | 1/4"        | <b>BP42</b>  | 50      |
| 1/2"    | 3/8"        | <b>BP43</b>  | 50      |
| 1/2"    | 1/2"        | <b>BP44</b>  | 25      |
| 1/2"    | 3/4"        | <b>BP46</b>  | 25      |
| 5/8"    | 3/8"        | <b>BP53</b>  | 25      |
| 5/8"    | 1/2"        | <b>BP54</b>  | 25      |
| 3/4"    | 1/2"        | <b>BP64</b>  | 25      |
| 3/4"    | 3/4"        | <b>BP66</b>  | 25      |
| 1"      | 3/4"        | <b>BP86</b>  | 10      |
| 1"      | 1"          | <b>BP88</b>  | 10      |



**male NPTF swivel x push-on hose barb**  
National Pipe Tapered - dryseal

| Hose ID | NPTF Thread | Part #          | Opt Qty |
|---------|-------------|-----------------|---------|
| 1/4"    | 1/8"        | <b>271-0402</b> | 100     |
| 1/4"    | 1/4"        | <b>271-0404</b> | 100     |
| 3/8"    | 1/4"        | <b>271-0604</b> | 50      |
| 3/8"    | 3/8"        | <b>271-0606</b> | 50      |
| 1/2"    | 3/8"        | <b>271-0806</b> | 25      |
| 1/2"    | 1/2"        | <b>271-0808</b> | 20      |
| 3/4"    | 3/4"        | <b>271-1212</b> | 10      |

Note: swivel is for assembly convenience only, not for live swivel applications.

### NPSM Swivel Hose Barb Fittings



**female NPSM swivel x push-on hose barb**  
gasket seat type

| Hose ID | NPSM | Part #          | Opt Qty |
|---------|------|-----------------|---------|
| 1/4"    | 1/8" | <b>280-0402</b> | 100     |
| 1/4"    | 1/4" | <b>280-0404</b> | 100     |
| 3/8"    | 1/4" | <b>280-0604</b> | 50      |
| 3/8"    | 3/8" | <b>280-0606</b> | 50      |
| 3/8"    | 1/2" | <b>280-0608</b> | 50      |
| 1/2"    | 1/2" | <b>280-0808</b> | 25      |
| 5/8"    | 1/2" | <b>280-1008</b> | 25      |
| 3/4"    | 3/4" | <b>280-1212</b> | 20      |



**female NPSM swivel x push-on hose barb**  
ball seat type

| Hose ID | NPSM | Part #        | Opt Qty |
|---------|------|---------------|---------|
| 1/4"    | 1/8" | <b>BPFS21</b> | 100     |
| 1/4"    | 1/4" | <b>BPFS22</b> | 50      |
| 1/4"    | 3/8" | <b>BPFS23</b> | 50      |
| 3/8"    | 1/4" | <b>BPFS32</b> | 50      |
| 3/8"    | 3/8" | <b>BPFS33</b> | 50      |
| 3/8"    | 1/2" | <b>BPFS34</b> | 50      |
| 1/2"    | 1/2" | <b>BPFS44</b> | 50      |
| 1/2"    | 3/4" | <b>BPFS46</b> | 25      |
| 3/4"    | 3/4" | <b>BPFS66</b> | 20      |

## Push-On Fittings



**Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.** No hose clamps or ferrules are needed. Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

### 45° SAE Hose Barb Fittings

#### male 45° SAE x push-on hose barb



| Hose ID | UNF Thread              | Brass Part #    |  | Opt Qty |
|---------|-------------------------|-----------------|--|---------|
| 1/4"    | 7/16"-20                | <b>282-0407</b> |  | 100     |
| 1/4"    | 1/2"-20                 | <b>282-0408</b> |  | 100     |
| 3/8"    | 5/8"-18 <sup>1</sup>    | <b>282-0610</b> |  | 50      |
| 1/2"    | 3/4"-16                 | <b>282-0812</b> |  | 50      |
| 5/8"    | 7/8"-14                 | <b>282-1014</b> |  | 25      |
| 3/4"    | 1-1/16"-14 <sup>1</sup> | <b>282-1217</b> |  | 25      |

<sup>1</sup> notch in hex for SAE identification

#### female 45° SAE swivel x push-on hose barb



| Hose ID | UNF Thread              | Brass Part #    |  | Opt Qty |
|---------|-------------------------|-----------------|--|---------|
| 1/4"    | 5/8"-18 <sup>1</sup>    | <b>284-0410</b> |  | 50      |
| 5/16"   | 5/8"-18 <sup>1</sup>    | <b>284-0510</b> |  | 50      |
| 3/8"    | 5/8"-18 <sup>1</sup>    | <b>284-0610</b> |  | 100     |
| 3/4"    | 1-1/16"-14 <sup>1</sup> | <b>284-1217</b> |  | 25      |

<sup>1</sup> notch in hex for SAE identification

### SAE Inverted Flare Fittings

#### male SAE swivel x push-on hose barb



| Hose ID | UNF4944 Thread | Brass Part #    |  | Opt Qty |
|---------|----------------|-----------------|--|---------|
| 1/4"    | 3/8"-24        | <b>290-0406</b> |  | 100     |
| 1/4"    | 7/16"-24       | <b>290-0407</b> |  | 100     |
| 1/4"    | 1/2"-20        | <b>290-0408</b> |  | 100     |
| 5/16"   | 1/2"-20        | <b>290-0508</b> |  | 50      |
| 5/16"   | 5/8"-18        | <b>290-0510</b> |  | 50      |
| 3/8"    | 1/2"-20        | <b>290-0608</b> |  | 100     |
| 3/8"    | 5/8"-18        | <b>290-0610</b> |  | 50      |
| 1/2"    | 3/4"-18        | <b>290-0812</b> |  | 50      |
| 5/8"    | 7/8"-18        | <b>290-1014</b> |  | 25      |

#### rigid female SAE x push-on hose barb



| Hose ID | UNF Thread | Brass Part #    |  | Opt Qty |
|---------|------------|-----------------|--|---------|
| 1/4"    | 3/8"-24    | <b>292-0406</b> |  | 100     |
| 1/4"    | 7/16"-24   | <b>292-0407</b> |  | 100     |
| 1/4"    | 1/2"-20    | <b>292-0408</b> |  | 100     |
| 5/16"   | 1/2"-20    | <b>292-0508</b> |  | 100     |
| 3/8"    | 1/2"-20    | <b>292-0608</b> |  | 100     |
| 3/8"    | 5/8"-18    | <b>292-0610</b> |  | 50      |
| 1/2"    | 3/4"-18    | <b>292-0812</b> |  | 25      |

## Push-On Fittings



**Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.** No hose clamps or ferrules are needed. Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

### 37° JIC Hose Barb Fittings

#### male 37° JIC x push-on hose barb

| Hose ID | UNF Thread | Brass Part #                 |  | Opt Qty |
|---------|------------|------------------------------|--|---------|
| 1/4"    | 7/16"-20   | <b>286-0407</b>              |  | 100     |
| 1/4"    | 1/2"-20    | <b>286-0408</b>              |  | 50      |
| 1/4"    | 9/16"-18   | <b>286-0409</b>              |  | 100     |
| 3/8"    | 9/16"-18   | <b>286-0609</b>              |  | 50      |
| 1/2"    | 3/4"-16    | <b>286-0812</b>              |  | 25      |
| 5/8"    | 7/8"-14    | <b>286-1014</b>              |  | 25      |
| 3/4"    | 1-1/16"-12 | <b>286-1217</b> <sup>1</sup> |  | 10      |

<sup>1</sup> UN thread



#### female 37° JIC swivel x push-on hose barb

| Hose ID | UNF Thread | Brass Part #                 |  | Opt Qty |
|---------|------------|------------------------------|--|---------|
| 1/4"    | 9/16"-18   | <b>288-0409</b>              |  | 50      |
| 5/16"   | 9/16"-18   | <b>288-0509</b>              |  | 50      |
| 3/8"    | 9/16"-18   | <b>288-0609</b>              |  | 50      |
| 1/2"    | 9/16"-18   | <b>288-0809</b>              |  | 25      |
| 3/4"    | 1-1/16"-12 | <b>288-1217</b> <sup>1</sup> |  | 10      |
| 1"      | 1-5/16"-12 | <b>288-1621</b> <sup>1</sup> |  | 10      |

<sup>1</sup> UN thread



| Hose ID | UNF Thread | 303 Stainless Part # |  | Opt Qty |
|---------|------------|----------------------|--|---------|
| 3/8"    | 9/16"-18   | <b>288-0609SS</b>    |  | 50      |
| 3/4"    | 1-1/16"-12 | <b>288-1217SS</b>    |  | 10      |
| 1"      | 1-5/16"-12 | <b>288-1621SS</b>    |  | 10      |

#### female 45°SAE / 37°JIC swivel x push-on hose barb (dual angle seat)

| Hose ID | UNF Thread | Brass Part #    |  | Opt Qty |
|---------|------------|-----------------|--|---------|
| 1/4"    | 7/16"-20   | <b>287-0407</b> |  | 100     |
| 1/4"    | 1/2"-20    | <b>287-0408</b> |  | 100     |
| 3/8"    | 1/2"-20    | <b>287-0608</b> |  | 25      |
| 3/8"    | 3/4"-16    | <b>287-0612</b> |  | 25      |
| 1/2"    | 3/4"-16    | <b>287-0812</b> |  | 25      |
| 1/2"    | 7/8"-14    | <b>287-0814</b> |  | 25      |
| 5/8"    | 7/8"-14    | <b>287-1014</b> |  | 25      |

| Hose ID | UNF Thread | 303 Stainless Part # |  | Opt Qty |
|---------|------------|----------------------|--|---------|
|         | 7/16"-20   | <b>287-0407SS</b>    |  | 100     |
| 1/2"    | 3/4"-16    | <b>287-0812SS</b>    |  | 25      |



#### female 37° JIC/45° SAE swivel x push-on 90° elbow

| Hose ID | UNF Thread | Plated Steel Part #             |  | Opt Qty |
|---------|------------|---------------------------------|--|---------|
| 1/4"    | 7/16"-20   | <b>289-0407</b> <sup>*</sup>    |  | 25      |
| 1/4"    | 7/16"-20   | <b>289-0407SAE</b> <sup>1</sup> |  | 25      |
| 3/8"    | 9/16"-18   | <b>289-0609</b> <sup>*</sup>    |  | 25      |
| 3/8"    | 5/8"-18    | <b>289-0610SAE</b> <sup>1</sup> |  | 25      |
| 1/2"    | 3/4"-16    | <b>289-0812</b> <sup>*</sup>    |  | 10      |
| 1/2"    | 3/4"-16    | <b>289-0812SAE</b> <sup>1</sup> |  | 10      |
| 3/4"    | 1-1/16"-12 | <b>289-1217</b> <sup>*2</sup>   |  | 5       |

<sup>1</sup> notch in nut for SAE identification

<sup>2</sup> UN thread

<sup>\*</sup> JIC only, may substitute dual angle



## Push-On Fittings



**Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.** No hose clamps or ferrules are needed. Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

### Rigid Tube x Push-On Hose Barb



| Hose ID | Tube OD | Brass Part #    |  | Opt Qty |
|---------|---------|-----------------|--|---------|
| 1/4"    | 3/16"   | <b>294-0403</b> |  | 100     |
| 1/4"    | 1/4"    | <b>294-0404</b> |  | 100     |
| 1/4"    | 5/16"   | <b>294-0405</b> |  | 100     |
| 3/8"    | 3/8"    | <b>294-0606</b> |  | 50      |
| 1/2"    | 1/2"    | <b>294-0808</b> |  | 50      |
| 5/8"    | 5/8"    | <b>294-1010</b> |  | 25      |
| 3/4"    | 3/4"    | <b>294-1212</b> |  | 25      |

### Push-On Hose Menders



| Hose ID | Brass        |               | 303 Stainless |     | Opt Qty |
|---------|--------------|---------------|---------------|-----|---------|
|         | Part #       | Price/E       | Part #        |     |         |
| 1/4"    | <b>BPM2</b>  | <b>\$2.81</b> | <b>SSPM2</b>  |     | 100     |
| 5/16"   | <b>BPM25</b> | <b>3.16</b>   | ---           | --- | 100     |
| 3/8"    | <b>BPM3</b>  | <b>3.36</b>   | <b>SSPM3</b>  |     | 50      |
| 1/2"    | <b>BPM4</b>  | <b>5.31</b>   | <b>SSPM4</b>  |     | 50      |
| 5/8"    | <b>BPM5</b>  | <b>7.65</b>   | ---           | --- | 25      |
| 3/4"    | <b>BPM6</b>  | <b>9.06</b>   | ---           | --- | 25      |
| 1"      | <b>BPM8</b>  | <b>15.38</b>  | ---           | --- | 10      |

### 90° Push-On Hose Barb x Male NPTF Elbows - Forged



| Hose ID | NPTF Thread | Brass           |  | Opt Qty |
|---------|-------------|-----------------|--|---------|
|         |             | Part #          |  |         |
| 1/4"    | 1/8"-27     | <b>273-0402</b> |  | 100     |
| 1/4"    | 1/4"-18     | <b>273-0404</b> |  | 50      |
| 3/8"    | 1/8"-27     | <b>273-0602</b> |  | 50      |
| 3/8"    | 1/4"-18     | <b>273-0604</b> |  | 50      |
| 3/8"    | 3/8"-18     | <b>273-0606</b> |  | 25      |
| 1/2"    | 3/8"-18     | <b>273-0806</b> |  | 25      |
| 1/2"    | 1/2"-14     | <b>273-0808</b> |  | 25      |
| 3/4"    | 1/2"-14     | <b>273-1208</b> |  | 10      |
| 3/4"    | 3/4"-14     | <b>273-1212</b> |  | 10      |

## Tool for Push-On Fittings



#### Assembly Instructions:

1. Trim hose end with smooth square cut
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

#### Features:

- cuts push-on style hose and inserts the fitting
- Built-in cutter slices through 1/4" - 3/4" ID reinforced push-on hose without fraying.
- Clamp hose into tool's vice and apply light pressure on handle to drive in the fitting.
- tool has four 7/16" diameter mounting holes for bench mounting
- overall size is 13-1/2" long x 2-3/8" wide x 7" height

| Size        | Part #       |
|-------------|--------------|
| 1/4" - 3/4" | <b>270AT</b> |

#### Disassembly Instructions:

1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.



**Caution:** Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

## Hose Assembly Tool



- installs 1/4", 5/16" and 3/8" hose fittings
- lightweight, portable, comfortable cushioned grip
- economical

| Part #      |
|-------------|
| <b>HHCI</b> |