



The Right Connection™

Maintenance and Repair

KORD INDUSTRIAL INC. 866.874.5673

Maintenance and Repair



Sealants

Megaboost Grease Gun

Features:

- threaded barrel eliminates cross threading, reload twice as fast
- clears clogged fittings in seconds
- volume mode - 20% more grease per stroke
- automatic bleeder valve makes this gun easy to prime
- grip allows for ergonomic one or two handed operation
- 3-way loading: filler nipple, cartridge, bulk
- combination filler nipple/air bleeder valve

Part #
L1185L



Thread Sealant Paste

Feature:

- temperature range: **-300°F to 500°F**

Can Size	Part #	Opt Qty
¼ pint	LCTS14	12
½ pint	LCTS1	24
1 pint	LCTS2	12
1 quart	LCTS3	12



Industrial PTFE Tape (White)

Features:

- thickness: 3.5 mil (0.0035 mm)
- temperature range: **-212°F to 500°F**

Size	Length	Part #	Opt Qty
½"	260"	TTA50	500
½"	520"	TTB50	500
½"	1296"	TTC50	500
¾"	260"	TTA75	350
¾"	520"	TTB75	350
1"	520"	TTB100	250



Stainless Steel PTFE Tape (Gray)

Features:

- thickness: 4 mil
- temperature range: **-58°F to 600°F**
- useful on stainless steel threaded joints or connections
- PTFE with nickel added
- nickel acts like a ball bearing

Size	Length	Part #	Opt Qty
½"	260"	TTA50SS	10



Industrial Heavy Duty PTFE Tape (Pink)

Features:

- thickness: 4 mil
- temperature range: **-400°F to 500°F**

Size	Length	Part #	Opt Qty
½"	540"	TTBP50	330



PTFE Tape for LP Gas (Yellow)

Features:

- thickness: 4 mil
- service temperature: **500°F (260°C)**
- Underwriters Listed

Size	Length	Part #	Opt Qty
½"	260"	TTA50LP	500



Joint Sealant Gasket Material

Features:

- GORE-TEX® interchangeable
- Form-In-Place expanded PTFE gasket material with adhesive backing
- manufactured from 100% virgin PTFE
- unaffected by all common chemicals (pH from 0-14)
- unlimited shelf life
- resilient with low cold flow
- requires less force than standard gasket materials
- pressure range from vacuum to 3000 PSI
- temperature range: **-450°F to 600°F**
- made in the USA
- larger spools are available, consult factory for price and availability
- FDA compliant #21CFR177.1550



Size	Length	Part #
1/4"	20'	LCJS4-20
1/4"	50'	LCJS4-50
3/8"	25'	LCJS6-25
1/2"	15'	LCJS8-15
3/4"	15'	LCJS12-15

Leak Detector

Features:

- detects leaks by forming bubbles which remain for up to ten minutes
- will not cause corrosion or deterioration
- color: fluorescent yellow
- non-toxic, non-freezing
- temperature range: **-7°F (-20°C) to 180°F (82°C)**
- meets Federal specification MIL-L-25567-C



Size	Part #	Case Qty
8 oz.	LCLD	24

Dixon Coupling Lubricant

Application:

- For use in assembly operations involving natural or synthetic rubber or plastic. Also an excellent lubricant when rubber or plastic needs to be cut, machined, pressed, turned, trimmed or ground.

Feature:

- biodegradable lubricant for coupling shanks



DCL20

DCL80

Size	Part #
1 liter	DCL20
4 liters	DCL80

WD-40 Smart Straw

Features:

- permanently attached straw
- flip up for a precision spray; flip down for regular spray action
- sold in case quantities only
- should not be used as a lubricant for coupling shanks



Size	Part #	Case Qty
11 oz.	WD40	12



Coupling Inserter for Large Hose

Features:

- portable
- inserts 4", 5", 6", 8", 10" and 12" couplings
- includes CI96AH pump (shown below)
- coupling inserter pusher plates (not shown) must be purchased separately

Part #	
CI9	

Hose ID	Part #
4" - 5"	45CIPUSH
6" - 8"	68CIPUSH
10" - 12"	1012CIPUSH



Coupling Inserters

Application:

- for insertion of hose shanks into hose with a 2¾" to 7¼" OD

Description	Part #
Supplied with a 10,000 PSI hand pump and 5 ton ram	CI96
Supplied with a 10,000 PSI air/hydraulic pump and 5 ton ram	CI96AH
Small jaws for 1" to 3" OD hose	CI9311SML



CI96AH



CI96

Hand Hydrotest Pump

Application:

- designed for use in testing pipe lines, pressure tanks and pressure vessels

Features:

- stainless steel piston, aluminum body
- uses efficient and long lasting check valves
- cylinder displacement: 1.37 cubic inches
- 0-1000 PSI pressure gauge, 10' pressure hose and quick disconnect coupler included
- piston: 7/8" with 2" stroke

Inlet NPT	Outlet NPT	Working Pressure PSI	Part #
½"	½"	1000	HHTP



Hung Up On Dixon Hose Racks

Application:

- can be used for fire or water hose

Features:

- aluminum rack can be easily mounted
- single and double racks have 5 pre-drilled 5/16" mounting holes
- two racks can be bolted face to face to create extra hose capacity
- single rack overall dimensions 19-1/2" x 6" x 9-3/16"
- double rack overall dimensions 19-1/2" x 12" x 9-3/16"

Description	Weight (lbs.)	Part #
single hose rack	3.5	DHR1
double hose rack	9.5	DHR2

DHR1
single hose rackDHR2
double hose rack
(hose not included)

Hydrostatic Test Pumps

A safe, cost effective pump to test hose before putting it into service.

Electric


Features:

- 1.3 GPM fill rate
- test pressure: **200 to 2000 PSI**
- suction strainer keeps dirt out of pump
- high pressure test gauge
- 115v motor
- 2 ft. power cord
- easy to use, portable

Pneumatic


Features:

- 5.5 GPM fill rate
- test pressure: **0 to 1500 PSI**
- stainless interior
- air gauge for quick, easy adjustment of maximum test pressure
- high pressure test gauge
- filter/regulator for clean, dry air to ensure long life of unit
- on - off valve for air input
- 15 ft. of hose included
- easy to use, portable
- Use of coalescing filter and water filter recommended for prolonged life.

Description	Part #
electric test pump	ETP

Description	Part #
pneumatic test pump	PTP

Hydrostatic Test Pump Accessories

Features:

- cost effective, pre-assembled caps or plugs to allow quick set up for testing hoses
- Caps and plugs come equipped with ½" brass straight-through plugs for quick attachment to the intermediate hose on the test pump (Pneumatic Test Pump) and bleed-off valve.

cam & groove test caps for male adapters

Size	Iron Part #
1"	ID100TC
1½"	ID150TC
2"	ID200TC
3"	ID300TC
4"	ID400TC

cam & groove test plugs for female couplers

Size	Iron Part #
1"	IA100TP
1½"	IA150TP
2"	IA200TP
3"	IA300TP
4"	IA400TP

female NPT test caps

Size	Iron Part #
1"	NPT100TC
1½"	NPT150TC
2"	NPT200TC
3"	NPT300TC
4"	NPT400TC

male NPT test plugs

Size	Iron Part #
1"	100TP
1½"	150TP
2"	200TP
3"	300TP
4"	400TP

bleed-off valve

Description	Part #
for pneumatic test pump	IBV50BOV

FRL Attachment Accessories

Description	Part #
3/8" Wilkerson modular coalescing filter (automatic drain)	M16-03A
3/8" Wilkerson modular coalescing filter (manual drain)	M16-03M
modular sleeve needed to connect M16-03A or M16-03M	GPA-95-292

Spill Kits

Features:

- easily stored behind a seat or in a storage compartment allowing drivers to act quickly when responding to a spill
- Poly-zip bag and bucket kits feature:
 - 10 pads (15" x 19")
 - 3 socks (3" x 4')
 - 2 disposal bags with ties
 - 1 pair Nitrile gloves

Part #	Description
DSK5-O	oil only, in 6½ gallon pail
DSK5-U	universal, in 6½ gallon pail
DSKB-O	oil only, in clear poly bag with zipper
DSKB-U	universal, in clear poly bag with zipper



universal spill kit



oil spill kit

Heavy-Duty Lava Hand Cleaner

Features:

- heavy duty hand cleaner with pumice
- 7.5 fl oz pump bottle
- sold in case quantity only

Part #	Case Qty
LAVA221	12



Marking Pens

Features:

- marks on wood, glass, paper, metal, and many other surfaces
- permanent mark
- unique valve action prevents tip drying

Color	Part #
black	BK91
white	WT91
yellow	YW91



Dixon Soft Hose Mallet

Features:

- soft mallet for pounding metal objects without damaging them
- The head material will not crack and is firmly attached to strong shaft-handle.
- length: 23"
- weight: 10 lbs.

Part #
DCM1



Dixon Hose Knife

Features:

- for fast cutting of rubber hose and belting
- guard protects hand while cutting

Part #
DRK15



Diameter Tape

Features:

- 6' tape for quickly finding the outside diameter of any cylindrical object
- converts circumference to OD at the measured point
- ABS case

Part #
DDT1



Stretch Straps

Features:

- durable tie down straps
- made of EPDM
- length does not include S-hooks
- S-hooks are steel



Length	Part #
10"	SSE10
15"	SSE15
21"	SSE21
31"	SSE31
41"	SSE41


WARNING!!

Failure to comply with this warning may result in serious damage and/or personal injury.
Maximum end to end safe stretch = 150% of length

- do not exceed maximum safe stretch
- inspect before each use, do not use if strap is cut, cracked or abraded
- inspect hooks for damage and/or wear. Replace if needed.
- protect strap from sharp edges or heat.
- wear eye protection during use
- do not use this product as the primary tie down
- refer to federal or state regulations for proper tie down methods

Safety Tag

Features:

- Dixon strongly recommends the use of a safety tag or warning label on all hose assemblies.
- sold in quantities of 100 only



Size	Part #
5" x 2-3/8"	DWL100


WARNING!!

- worn-out hose fittings should be replaced
- loose clamps on hose can be dangerous
- bolt type clamps should be retensioned regularly
- for extra safety, retaining devices such as clips, chains or cables must be used

Safety Tape

Features:

- Dixon strongly recommends the use of a safety tag or warning label on all hose assemblies.
- length of tape - 55 yards, approximately 255 warnings



Size	Part #
1 1/2"	DSTW


WARNING!!

- worn-out hose fittings should be replaced
- loose clamps on hose can be dangerous
- bolt type clamps should be retensioned regularly
- for extra safety, retaining devices such as clips, chains or cables must be used

Weatherproof First Aid Kit

Features:

- polypropylene case
- kit supports 25 persons
- each kits includes:
adhesive strips, large wound pads, eye pads, triangular bandage, first aid / burn cream, eye flush, elastic bandages, scissors, forceps, first aid instructions, gauze pads, adhesive tape, antiseptic towelettes, aspirin, cold pack, latex exam gloves
- 10 person and 50 person kits are also available, consult the factory for price and availability



Weight	Part #
1.8 lbs.	FAK25P