

Sand Blast Hose Natural Rubber Tube Series 7244

Series 7244 is designed to blast sand and other abrasive materials to clean, condition or strip cement, steel, stone and other materials in a variety of applications. The thick, static dissipating natural rubber tube provides abrasion resistance and a heavy wall provides kink resistance. The blended rubber cover is resistant to abrasion and weathering.

Tube:	Black natural rubber; static dissipating
Reinforcement:	Multiple textile plies
Cover:	Black synthetic rubber blend
Temp. Range:	-20°F to +160°F (-29°C to +71°C)
Brand Method:	Embossed
Brand Example:	PARKER SERIES 7244 SAND BLAST HOSE 150 PSI WP
Design Factor:	3:1
Industry Standards:	None applicable
Applications:	 Abrasive materials, sand
	• Clean, condition or strip cement, steel, stone and other materials
	 Construction, general industrial, shipyards
Vacuum:	Not recommended
Compare to:	Kuriyama Sand Blast; Veyance Plicord Blast; XF Blast
Packaging:	Coils

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (Ibs/ft)	Approx Wt (kg/ft)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)
7244-500	1/2	12.7	2	1.055	26.8	0.33	0.15	150	10.3	50
7244-750	3/4	19.1	4	1.500	38.1	0.65	0.29	150	10.3	50
7244-1000	1	25.4	4	1.860	47.3	1.00	0.45	150	10.3	50
7244-1250	1-1/4	31.8	4	2.170	53.8	1.25	0.57	150	10.3	50
7244-1500	1-1/2	38.1	4	2.360	60.0	1.30	0.59	150	10.3	50
7244-2000	2	50.8	4	2.870	72.8	1.75	0.79	150	10.3	50