

DRAGON BREATH® Hot Air Blower Hose Series SW360

Series SW360 is a heavy duty, high pressure hot air blower hose designed for bulk loading/ unloading of dry materials in plants or transport vehicles. The hose transfers hot air from a compressor to the storage bin/cargo bay to propel bulk product. The hose construction incorporates a tube that features a temperature rating to $350^{\circ}F(177^{\circ}C)$ and resists drying out. The dual wire helix provides full suction capability, kink resistance, flexibility for ease of handling and a path to conduct a static electrical charge to ground. The cover resists abrasion, heat and ozone.

NOTE: For larger diameter hose, refer to Series EW360.

Tube: Reinforco Cover: Temp. Ra Brand Ma Brand Ex	inge: ethod	:	Black EPDM Multiple textile plies with dual wire helix Black EPDM; wrapped finish -40°F to +350°F (-40°C to +177°C) Black text on yellow stripe PARKER SERIES SW360 DRAGON BREATH® HOT AIR BLOWER HOSE XXX PSI WP (CAUTION) MADE IN USA								
Design Factor: Applications:			4:1 Hot air blower systems 								
Compare to:			 In-plant transfer; delivery, loading/unloading General industrial, transportation Eaton Boston Wildcat Hot Air; Gates Hot Air Blower; Veyance Plicord Torrid Air 								
Vacuum:			Full								
Packagir	ıg:		Coils								
	einf lies	OD (in)	OD (mm)	Approx Wt (Ibs/ft)	Approx Wt (kg/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	

								(in)	(mm)			(11)
SW360-2000	2	50.8	2	2.500	63.5	1.08	0.49	6.0	152.4	200	13.8	100
SW360-3000	3	76.2	2	3.563	90.5	1.78	0.81	12.0	304.8	200	13.8	100
SW360-4000	4	101.6	2	4.563	115.9	2.46	1.12	16.0	406.4	125	8.6	100
SW360-6000	6	152.4	2	6.813	173.0	5.00	2.27	24.0	609.6	100	6.9	100

WARNINGS!

Part

Number

ID

(in)

,, Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

" Do not use with cam and groove couplings, which are designed for use with liquids.