

ULTRA-LOK®

The Ultimate Clamping System

Ultra-Lok® Preformed Clamp

| Part No. | Material* | Width | | Thickness | | Inside Diameter | | Package Quantity | Package Weight | |
|----------|-----------------|-------|------|-----------|------|-----------------|-----|------------------|----------------|------|
| | | In | mm | In | mm | In | mm | | Lbs | Kg |
| UL2799** | 201 SS 1/4 Hard | 1/2 | 12.7 | 0.030 | 0.76 | 1 1/2 | 38 | 100/box | 9.1 | 4.1 |
| UL2839** | 201 SS 1/4 Hard | 1/2 | 12.7 | 0.030 | 0.76 | 2 | 508 | 100/box | 10.6 | 4.8 |
| UL2869** | 201 SS 1/4 Hard | 1/2 | 12.7 | 0.030 | 0.76 | 2 3/4 | 69 | 100/box | 12.7 | 5.8 |
| UL2919** | 201 SS 1/4 Hard | 1/2 | 12.7 | 0.030 | 0.76 | 4 | 101 | 100/box | 16.7 | 7.6 |
| UL2279 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 2 | 50 | 100/box | 14.9 | 6.8 |
| UL2109 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 2 3/4 | 69 | 50/box | 9.2 | 4.2 |
| UL2119 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 3 | 76 | 50/box | 10.4 | 4.7 |
| UL2129 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 3 1/2 | 88 | 50/box | 10.8 | 4.9 |
| UL2139 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 4 | 101 | 25/box | 6.4 | 2.9 |
| UL2149 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 4 1/2 | 114 | 25/box | 7.0 | 3.2 |
| UL2159 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 5 | 127 | 25/box | 7.5 | 3.4 |
| UL2709 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 5 1/4 | 139 | 25/box | 7.3 | 3.3 |
| UL2169 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 6 | 152 | 25/box | 8.4 | 3.8 |
| UL2179 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 6 1/2 | 165 | 25/box | 10.2 | 4.6 |
| UL2189 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 7 | 177 | 25/box | 9.8 | 4.4 |
| UL2199 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 8 | 203 | 25/box | 11.0 | 5.0 |
| UL2289 | 201 SS 1/4 Hard | 3/4 | 19.1 | 0.030 | 0.76 | 9 | 228 | 10/box | 5.1 | 2.31 |

**1/2" bands require M09387 for UL4000 or UL9010 tools
Also available in Ultra-Lok® Band see page 10



Ultra-Lok®
Preformed Clamp

Ultra-Lok® Tools

| Part No. | Description | Package Quantity | Package Weight | |
|----------|--|------------------|----------------|-----|
| | | | Lbs | Kg |
| UL4000 | Ultra-Lok® 18-volt Rechargeable, Portable Tool | each | 17.8 | 6.7 |
| UL9010 | Ultra-Lok® 110-volt AC, Corded Electric Tool | each | 18.3 | 8.4 |
| ULK249 | Kit; Used to upgrade the tension body of the UL9000 and the UL9010, includes 3/4" and 1/2" shear plates | each | 0.4 | 0.2 |
| M09387 | 1/2" Shear plate for UL4000, upgraded UL9000 and UL9010 to convert from 3/4" Ultra-Lok® to 1/2" Ultra-Lok® Clamp Systems | each | 0.1 | 0.1 |

UL9010 Ultra-Lok® Electric Tool

- Ultra-Lok® clamps 1/2" + & 3/4" either preformed or Band and Buckle can be applied.
- Locks under full tension.
- Adjustable speed and torque.
- Consistent, repeatable tensioning.
- Ideal for hose clamping.



Ultra-Lok® UL9010
Electric Tool

UL4000 Rechargeable or cordless Ultra-Lok® Tool

- Ultra-Lok® clamps 1/2" + & 3/4" either preformed or Band and Buckle can be applied.
- Designed for portable requirements.
- Consistent repeatable tensioning.
- Locks under full tension.
- Ultra-Lok® clamps can be applied four times faster than conventional clamps.
- Supplied with spare battery and charger with Automatic Tune-Up feature.



Ultra-Lok® UL4000
Rechargeable
Electric Tool

† For 1/2" Applications, must use M09387 1/2" Shear Plate.

