



Interlocked Stainless Steel and Galvanized Floppy Hose Protection Cover



KHI-IL-S STAINLESS STEEL 304

KHI-IL-G GALVANIZED STEEL

Hose I.D. Inches	Hose O.D. Inches	Wt. Per Foot Approx.
5/32"	.256"	0.052
3/16"	.285"	0.062
7/32"	.325"	0.092
1/4"	.345"	0.110
9/32"	.375"	0.120
5/16"	.405"	0.130
3/8"	.375"	0.160
1/2"	.600"	0.180
9/16"	.665"	0.185
5/8"	.725"	0.190
11/16"	.790"	0.200
3/4"	.850"	0.210
13/16"	.950"	0.230
7/8"	.980"	0.250
15/16"	1.040"	0.270



Packed



Unpacked

PACKING AVAILABILITY

All dimensions are based on the hose in the extended position and all weights are approximate.

Special swaged fittings available upon request.

Bronze or brass material is available upon request. Dimensions are the same as galvanized steel.

TYPE PACKING	PRESSURE RANGE	VACUUM	TEMPERATURE
COTTON	UP TO 15 PSI	UP TO 15 MERCURY	300 F
STAINLESS WIRE	UP TO 15 PSI	UP TO 15 MERCURY	1500 F
APYROUS	UP TO 15 PSI	UP TO 15 MERCURY	450 F
ELASTOMERIC	UP TO 20 PSI	UP TO 20 MERCURY	180 F