



SUPER-FLEX® GS

General Service Air & Water Hose

Series 7322 (Red) and Series 7323 (Black)

Series 7322/7323 is a versatile general purpose hose designed to handle air, mild chemicals and water. The hose incorporates a tube that is compatible with light oil mists, and features a rigid mandrel construction that produces a *true* round, concentric profile for superior coupling fit and retention. The cover is resistant to abrasion, heat and ozone.

NOTE: Do not with use with oil or refined fuel.

- Tube:** Black EPDM; ARPM Class C oil resistance
- Reinforcement:** Multiple textile plies
- Cover:** **7322:** Red EPDM, wrapped finish
7323: Black EPDM, wrapped finish
- Temp. Range:** -40°F to +212°F (-40°C to +100°C)
- Brand Method:** **7322:** White text on red stripe
7323: White text on black stripe
- Brand Example:** PARKER SERIES (7322) (7323) SUPER-FLEX® GS
200 PSI MAX WP GENERAL SERVICE MADE IN USA
- Design Factor:** 4:1
- Vacuum:** Not recommended
- Industry Standards:** ARPM Class C oil resistant tube
- Applications:**
 - Air (including oil mist), mild chemicals, water
 - Agriculture, construction, general industrial
- Compare to:** Gates AdaptaFlex; Veyance Horizon
- Packaging:** Coils, reels ("A" part numbers)

Series 7322 (Red) and Series 7323 (Black)

Part Number 7322 or 7323	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kg/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)
-125200	1-1/4	31.8	2	1.741	44.2	0.71	0.32	7.5	190.5	200	13.8	43	200
-150200	1-1/2	38.1	2	1.985	50.4	0.82	0.37	8.5	215.9	200	13.8	43	200
-200200	2	50.8	4	2.568	65.2	1.23	0.56	12.0	304.8	200	13.8	43	200