

SPIRALITE® 1200

CORRUGATED RUBBER DUCT HOSE

- **APPEARANCE/CONSTRUCTION:**
Rubber tube with black PVC helix.
Corrugated cover, smooth interior.

- **BENEFITS:**
 - Lightweight and durable.
 - Static-dissipating tube.

- **GENERAL APPLICATIONS:**
 - Material handling.
 - Air, abrasive dust ducting.
 - Light abrasive suction.

- **TEMPERATURE RANGE:**
-30°F to +140°F

- **STANDARD LENGTHS:**
2" thru 6" 100ft.
8" 50ft.

NOMINAL SIZE	inch	2"	2 1/2"	3"	4"	5"	6"	8"
APPROX. O.D.	inch	2.37	2.91	3.48	4.55	5.65	6.78	8.87
RECOMMENDED W.P. AT 68°F	psi	35	30	30	25	25	25	20
VACUUM RATING AT 68°F	in/HG	28	28	28	25	25	25	25
RECOM. MIN. BEND RADIUS AT 68°F*	inch	4	5	6	9	10	12	17
APPROX. B.P. AT 68°F	psi	105	90	90	75	75	75	60
APPROX. WT.	lbs./ft.	.49	.66	.91	1.36	2.08	2.86	4.23

* BEND RADIUS FOR CONTINUOUS SERVICE.