



SPIRALITE® 120

PVC GREEN STANDARD SUCTION HOSE

- **APPEARANCE/CONSTRUCTION:**
Green PVC with white helix.
Corrugated cover, smooth interior.

- **BENEFITS:**

- Good combination of durability and flexibility.
- Smooth interior prevents material blockage.

- **GENERAL APPLICATIONS:**

- General suction for water & light chemical solutions.

- **TEMPERATURE RANGE:**

-10°F to +130°F

- **STANDARD LENGTHS:**

1-1/2" thru 6" 100ft.
8" and above 20' 25' 30'

NOMINAL SIZE	inch	1 1/2"	2"	2 1/2"	3"	4"	6"	8"	10"	12"
APPROX. O.D.	inch	1.87	2.41	2.98	3.54	4.65	6.98	9.14	11.30	13.31
APPROX. WT.										
RECOMMENDED W.P. AT 68°F	psi	50	40	40	35	35	35	35	30	25
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28	28	28	21	15
RECOM. MIN. BEND RADIUS AT 68°F*	inch	3	4	5	6	8	15	18	28	36
APPROX. B.P.	psi	150	120	120	105	105	105	105	90	75
AT 68°F	lbs./ft.	.38	.58	.79	1.07	1.70	4.26	6.57	9.37	11.11

* BEND RADIUS FOR CONTINUOUS SERVICE.