



SPIRALITE® 125

PVC CLEAR CORRUGATED SUCTION HOSE

NOMINAL SIZE	inch	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"	8"	10"	12"
APPROX. O.D.	inch	.99	1.26	1.61	1.86	2.44	2.98	3.54	4.65	5.73	6.98	9.14	11.30	13.27
RECOMMENDED W.P. AT 68°F	psi	50	35	50	50	40	40	35	35	30	35	35	30	25
VACUUM RATING AT 68°F	in/HG	28	28	28	28	28	28	28	28	28	28	28	21	15
RECOM. MIN. BEND RADIUS AT 68°F*	inch	1	2	3	3	4	5	6	8	11	15	18	28	36
APPROX. B.P. AT 68°F	psi	150	105	150	150	120	120	105	105	90	105	105	90	75
APPROX. WT.	lbs./ft.	.11	.14	.31	.37	.57	.77	1.04	1.65	2.34	4.08	6.34	9.10	10.14

* BEND RADIUS FOR CONTINUOUS SERVICE.

- **APPEARANCE/CONSTRUCTION:**

Clear PVC with white helix.
Corrugated cover, smooth interior.

- **BENEFITS:**

- Good combination of durability and flexibility.
- Smooth interior prevents material blockage.
- Clear wall allows easy inspection of material flow.

- **GENERAL APPLICATIONS:**

– General suction for water & light chemical solutions.

- **TEMPERATURE RANGE:**

-10°F to +130°F

- **STANDARD LENGTHS:**

3/4" thru 6" 100ft.
8" thru 12" 20' 25' 30'
8" also in 50'