



# SPIRALITE® 190

## PVC CLEAR CORRUGATED LIGHT DUCT HOSE

- **APPEARANCE/CONSTRUCTION:**  
Clear PVC wall with white helix. Corrugated wall, and smooth interior.

- **BENEFITS:**  
– Lightweight and highly flexible.

- **GENERAL APPLICATIONS:**  
– Air ducting and dust control.  
– Transferring light abrasives.  
– Also available in Flame Resistant (UL 94V0 & USMSHA 2G-26/1) formulations on special orders.

- **STANDARD LENGTHS:**  
1" thru 6"                    100ft.  
8"                                50ft.  
10"                               25ft.

| NOMINAL SIZE                     | inch     | 1"   | 1 1/4" | 1 1/2" | 2"   | 2 1/2" | 3"   | 4"   | 5"   | 6"   | 8"   | 10"   |
|----------------------------------|----------|------|--------|--------|------|--------|------|------|------|------|------|-------|
| APPROX. O.D.                     | inch     | 1.25 | 1.52   | 1.79   | 2.35 | 2.90   | 3.45 | 4.50 | 5.54 | 6.54 | 8.57 | 10.61 |
| RECOM. MIN. BEND RADIUS AT 68°F* | inch     | 1    | 2      | 2      | 2    | 3      | 3    | 4    | 5    | 5    | 7    | 13    |
| APPROX. WT.                      | lbs./ft. | .15  | .20    | .24    | .39  | .54    | .72  | 1.02 | 1.26 | 1.51 | 2.21 | 2.75  |