



# WILDCATTER®

## Hot Oiler Hose

### Series 7301

Series 7301 is a heavy duty, high pressure hose for hot oil at 275°F continuous/300°F intermittent (135°C/149°C). The hose construction incorporates multiple wire braids of reinforcement for crush resistance, durability, kink resistance and a path to conduct a static electrical charge to ground. The cover is resistant to abrasion, heat, oil and weathering.

- Tube:** Black chloroprene  
**Reinforcement:** Multiple wire braids  
**Cover:** Black chloroprene; wrapped finish  
**Temp. Range:** -40°F to +275°F/300°F (-40°C to +135°C/149°C)  
**Brand Method:** Red text on black stripe  
**Brand Example:** PARKER SERIES 7301 WILDCATTER HOT OILER HOSE (ID)  
 2250 PSI MAX WP TEMP RATING 275°F CONTINUOUS  
 300°F INTERMITTENT 001 (DATE CODE)
- Design Factor:** 3:1  
**Industry Standards:** None applicable  
**Applications:**
- Hot asphalt, glue, tar, oil, wax
  - In-plant transfer; delivery trucks
  - Construction, general industrial, oil field
- Vacuum:** Not recommended  
**Packaging:** Coils

Part Number	ID (in)	ID (mm)	Reinf Braids	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kg/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)	Stock Status **
7301-1502	1-1/2	38.1	2	2.000	50.8	1.59	0.72	13.0	330.2	2250	155.1	71	50	Y
7301-1502075	1-1/2	38.1	2	2.000	50.8	1.59	0.72	13.0	330.2	2250	155.1	71	75	Y

**⚠ WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. [Refer to the NAHAD Industrial Hose Assembly Guidelines.](#)