



# Dry Cement Hose

## 3/16" SBR Tube

### Series SS147

Series SS147 is a lightweight, low pressure discharge hose for dry abrasive materials such as cement and powders. The static dissipating 3/16" SBR tube provides abrasion resistance and the SBR cover is resistant to abrasion, cuts, scuffs and weathering.

- Tube:** 3/16" Black SBR; static dissipating  
**Reinforcement:** Multiple textile plies  
**Cover:** Black SBR; wrapped finish  
**Temp. Range:** -40°F to +180°F (-40°C to +83°C)  
**Brand Method:** Black text on green stripe  
**Brand Example:** PARKER SERIES SS147 DRY MATERIAL DISCHARGE HOSE 60 PSI WP MADE IN USA  
**Design Factor:** 4:1  
**Industry Standards:** None applicable  
**Applications:**
  - Abrasive dry materials, cement, lime, powders, silica
  - In-plant transfer/loading, bulk transport trucks
  - Construction, general industrial**Vacuum:** Not recommended  
**Compare to:** Boston Lynx HD; Gates Dry Cement Delivery; Thermoid Transporter; Veyance Black Softwall  
**Packaging:** Coils

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kg/ft)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)
SS147-4000	4	101.6	2	4.625	117.5	1.96	0.89	60	4.1	100

**⚠ WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. [Refer to the NAHAD Industrial Hose Assembly Guidelines.](#)