

H5000A

ISOBARIC SPIRAL HOSE
350 BAR / 5100 PSI
MILLION CYCLE



RECOMMENDED FOR:

Very high pressure hydraulic oil lines.
Constant pressure (Isobaric) 350 bar / 5100 psi in all sizes.
Small bend radius is an advantage in installations.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of:
EN 856 Type R13, ISO 18752-CC, SAE 100R13.

TUBE:

Black, oil resistant synthetic rubber.

REINFORCEMENT:

Four (-06 to -20 size) and six (-24 to -32 size) alternating layers of spiralled high tensile steel wire.

COVER:

AVENGER™ Black, oil and abrasion resistant synthetic rubber. Flame Resistant & MSHA compliant. Highly visible layline branding for easy and permanent identification. No skiving required with T7000 and T9000 Series BITELOK Crimp Couplings.

FEATURES:

Tested to **1 million impulse cycles** at up to 1/2 SAE 100R13 Minimum Bend Radius. Constant pressure 350 bar / 5100 psi in all sizes for easy system design and hose selection. Small bend radius is an advantage in installations.

MSHA - FLAME RESISTANCE:

AVENGER™ complies with Flame Resistant requirements of Australian Standard AS 2660 and Method of Test AS 1180.10B. Meets Flame Resistant Designation "U.S. MSHA" of the US Department of Labor, Mine Safety and Health Administration.

TEMPERATURE RANGE:

-40°C to +121°C, -40°F to +250°F.

WORKING PRESSURE:

Maximum working pressures are based on 4:1 safety factor (maximum working pressure to minimum burst pressure).

THIRD PARTY APPROVALS:

ABS, DNV, GL, LR, MED and USCG.

COUPLINGS:

BITELOK NON-SKIVE ONE-PIECE CRIMP

T7000 Series (sizes -06 to -24)

T9000 Series (size -32)

H5000A - AVENGER ISOBARIC SPIRAL HOSE															
PART NO	HOSE SIZE	NOMINAL HOSE ID	NOMINAL HOSE OD	MAXIMUM WORKING PRESSURE	MINIMUM BURST PRESSURE	MINIMUM BEND RADIUS	AVERAGE WEIGHT	COUPLING SERIES ONE PIECE							
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE
H5006A	10	-06	9,5	3/8	19,3	0.76	350	5100	1400	20400	62	2.4	0,61	0.41	T7000
H5008A	12	-08	12,7	1/2	22,7	0.89	350	5100	1400	20400	90	3.5	0,78	0.52	T7000
H5010A	16	-10	15,9	5/8	26,2	1.03	350	5100	1400	20400	100	3.9	0,98	0.66	T7000
H5012A	19	-12	19,1	3/4	29,6	1.17	350	5100	1400	20400	120	4.7	1,21	0.81	T7000
H5016A	25	-16	25,4	1	36,8	1.45	350	5100	1400	20400	150	5.9	1,72	1.16	T7000
H5020A	31	-20	31,8	1.1/4	45,0	1.77	350	5100	1400	20400	210	8.3	2,42	1.63	T7000
H5024A	38	-24	38,1	1.1/2	52,7	2.07	350	5100	1400	20400	330	13.0	3,44	2.31	T7000
H5032A	51	-32	50,8	2	67,5	2.66	350	5100	1400	20400	400	15.8	5,40	3.63	T9000

Refer to the latest RYCO Crimp Charts for crimp diameter and mark lengths.

RYCO QUALITY