

# ■ Ryco T9000 Series Hose End Catalog



# COUPLINGS

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS

### HOSE COMPATIBILITY FOR T9000 SERIES

#### NON-SKIVE

For RYCO Hose H5032, H6024, R4SH12, R4SH16.



#### BSP

**T9010**  
(T901)

**T9013**  
(T901P)

**T9020**  
(T902)

60° SEAT





HOSE SIZE		THRD SIZE	DASH SIZE	BSPT MALE	BSPP MALE	BSPP FEMALE			
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>
19	3/4	3/4	-1212	<b>T9010-1212</b>	42	<b>T9013-1212</b>	42	<b>T9020-1212</b>	27
25	1	1	-1616	<b>T9010-1616</b>	49	<b>T9013-1616</b>	46	<b>T9020-1616</b>	37
31	1.1/4	1.1/4	-2020	<b>T9010-2020</b>	54	<b>T9013-2020</b>	51	<b>T9020-2020</b>	41
38	1.1/2	1.1/2	-2424	<b>T9010-2424</b>	61	<b>T9013-2424</b>	55	<b>T9020-2424</b>	44
51	2	2	-3232	<b>T9010-3232</b>	64	<b>T9013-3232</b>	67	<b>T9020-3232</b>	53

#### BSP

**T9050**  
(T905)

**T9260**  
(T926)

60° SEAT





HOSE SIZE		THRD SIZE	DASH SIZE	BSPP FEMALE 90° ELBOW	BSPP FEMALE 90° TUBE BEND				
DN	inch	inch		PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9050-1212</b>	36	30			
25	1	1	-1616	<b>T9050-1616</b>	40	32	<b>T9260-1616</b>	71	71
31	1.1/4	1.1/4	-2020	<b>T9050-2020</b>	49	43	<b>T9260-2020</b>	86	91
38	1.1/2	1.1/2	-2424	<b>T9050-2424</b>	59	60			
51	2	2	-3232	<b>T9050-3232</b>	62	56			

#### NPT

**T9090**  
(T909)

**T9091**  
(T909E)

60° SEAT



HOSE SIZE		THRD SIZE	DASH SIZE	NPT MALE	NPT MALE EXTENDED (API)		
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>
19	3/4	3/4	-1212	<b>T9090-1212</b>	42		
25	1	1	-1616	<b>T9090-1616</b>	49		
31	1.1/4	1.1/4	-2020	<b>T9090-2020</b>	54		
38	1.1/2	1.1/2	-2424	<b>T9090-2424</b>	55		
51	2	2	-3232	<b>T9090-3232</b>	66	<b>T9091-3232</b>	107

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS



### CROCBITE

#### T9880

#### T9881

#### T9882

CROCBITE  
HIGH PRESSURE



HOSE SIZE		MWP	DASH SIZE	CROCBITE MALE	CROCBITE MALE 45° ELBOW			CROCBITE MALE 90° ELBOW			
DN	inch	bar		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	420	-1220	<b>T9880-1220</b>	47						
25	1	420	-1625	<b>T9880-1625</b>	66						
31	1.1/4	420	-2032	<b>T9880-2032</b>	68	<b>T9881-2032</b>	77	50	<b>T9882-2032</b>	52	94
38	1.1/2	420	-2440	<b>T9880-2440</b>	72	<b>T9881-2440</b>	86	53	<b>T9882-2440</b>	59	101
51	2	420	-3250	<b>T9880-3250</b>	102	<b>T9881-3250</b>	114	73	<b>T9882-3250</b>	73	135

### JIC





#### T9030 (T903)

#### T9040 (T904)

#### T9045 (T904V)

#### T9250 (T925)

37° FLARE



HOSE SIZE		THRD SIZE	TUBE SIZE	DASH SIZE	JIC MALE	JIC FEMALE		JIC FEMALE HIGH PRESSURE		JIC FEMALE 45° TUBE BEND			
DN	inch	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL
19	3/4	1.1/16	3/4	-1217	<b>T9030-1217</b>	43	<b>T9040-1217</b>	28			<b>T9250-1217</b>	66	22
19	3/4	1.5/16	1	-1221			<b>T9040-1221</b>	32					
25	1	1.5/16	1	-1621	<b>T9030-1621</b>	47	<b>T9040-1621</b>	34	<b>T9045-1621</b>	37	<b>T9250-1621</b>	78	30
31	1.1/4	1.5/8	1.1/4	-2026	<b>T9030-2026</b>	52	<b>T9040-2026</b>	44	<b>T9045-2026</b>	36	<b>T9250-2026</b>	96	39
38	1.1/2	1.7/8	1.1/2	-2430	<b>T9030-2430</b>	57	<b>T9040-2430</b>	49	<b>T9045-2430</b>	57	<b>T9250-2430</b>	121	50
51	2	2.1/2	2	-3240	<b>T9030-3240</b>	73	<b>T9040-3240</b>	60			<b>T9250-3240</b>	156	63

### JIC





#### T9255 (T925V)

#### T9243 (T924S)

#### T9240 (T924)

#### T9245 (T924V)

37° FLARE



HOSE SIZE		THRD SIZE	TUBE SIZE	DASH SIZE	JIC FEMALE HIGH PRESSURE 45° BEND			JIC FEMALE 90° SHORT BEND			JIC FEMALE 90° MEDIUM BEND			JIC FEMALE HIGH PRESSURE 90° MEDIUM BEND		
DN	inch	inch	inch		PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	1.1/16	3/4	-1217							<b>T9240-1217</b>	58	57			
19	3/4	1.5/16	1	-1221												
25	1	1.5/16	1	-1621	<b>T9255-1621</b>	85	35				<b>T9240-1621</b>	69	72	<b>T9245-1621</b>	69	72
31	1.1/4	1.5/8	1.1/4	-2026	<b>T9255-2026</b>	104	43				<b>T9240-2026</b>	88	81	<b>T9245-2026</b>	88	87
38	1.1/2	1.7/8	1.1/2	-2430	<b>T9255-2430</b>	127	55				<b>T9240-2430</b>	104	106	<b>T9245-2430</b>	103	111
51	2	2.1/2	2	-3240							<b>T9240-3240</b>	141	132			

# COUPLINGS

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS

### METRIC





**T9630**  
[T963]

**T9711**  
[T971]

**T9720**  
[T972]

**T9730**  
[T973]

**DKS/DKOS**  
**METRIC O RING (HEAVY)**



HOSE SIZE	THRD SIZE	TUBE SIZE	DASH SIZE	DKS MALE 24° CONE	DKOS FEMALE 24° CONE	DKOS FEMALE 24° CONE 45° TUBE BEND	DKOS FEMALE 24° CONE 90° TUBE BEND							
DN	inch	inch	inch	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	
19	3/4	36x2,0	25	-1236	<b>T9630-1236</b>	40	<b>T9711-1236</b>	33	<b>T9720-1236</b>	76	36	<b>T9730-1236</b>	57	88
25	1	42x2,0	30	-1642	<b>T9630-1642</b>	43	<b>T9711-1642</b>	35	<b>T9720-1642</b>	89	37	<b>T9730-1642</b>	70	77
31	1.1/4	52x2,0	38	-2052	<b>T9630-2052</b>	48	<b>T9711-2052</b>	39	<b>T9720-2052</b>	130	48	<b>T9730-2052</b>	91	89




### ORFS

**T9800**  
[T980]

**T9810**  
[T981]

**T9820**  
[T982]

**O RING**  
**FACE SEAL**





HOSE SIZE	THRD SIZE	TUBE SIZE	DASH SIZE	ORFS FEMALE	ORFS FEMALE 45° TUBE BEND	ORFS FEMALE 90° MEDIUM BEND						
DN	inch	inch	inch	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	
19	3/4	1.3/16	3/4	-1219	<b>T9800-1219</b>	44	<b>T9810-1219</b>	66	29	<b>T9820-1219</b>	55	59
25	1	1.7/16	1	-1623	<b>T9800-1623</b>	56	<b>T9810-1623</b>	87	34	<b>T9820-1623</b>	71	71
31	1.1/4	1.11/16	1.1/4	-2027	<b>T9800-2027</b>	59	<b>T9810-2027</b>	107	45	<b>T9820-2027</b>	87	90
38	1.1/2	2	1.1/2	-2432	<b>T9800-2432</b>	69						

### RKVP

**T9896**

**T9899**

**RKVP**  
**HIGH PRESSURE**



HOSE SIZE	RKVP SIZE	MAX WP	DASH SIZE	RKVP MALE	RKVP FEMALE		
DN	inch	mm	bar	PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>
19	3/4	20	420	-1220	57	<b>T9899-1220</b>	39
25	1	25	420	-1625	61	<b>T9899-1625</b>	48
31	1.1/4	32	420	-2032	75	<b>T9899-2032</b>	54
38	1.1/2	40	420	-2440	89	<b>T9899-2440</b>	60
51	2	50	420	-3250	82	<b>T9899-3250</b>	66

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS




### STAPLELOK

**T9870**  
(T987)

**T9871**  
(T988)

**T9872**  
(T989)

STAPLE  
O RING & BACK UP RING  
SUPPLIED




HOSE SIZE		STAPLE SIZE	DASH SIZE	STAPLELOK MALE	STAPLELOK MALE 45° ELBOW			STAPLELOK MALE 90° ELBOW			
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	20	-1220	<b>T9870-1220</b>	39	<b>T9871-1220</b>	59	33	<b>T9872-1220</b>	37	56
25	1	25	-1625	<b>T9870-1625</b>	49	<b>T9871-1625</b>	64	37	<b>T9872-1625</b>	46	68
31	1.1/4	32	-2032	<b>T9870-2032</b>	49	<b>T9871-2032</b>	65	37	<b>T9872-2032</b>	48	68
38	1.1/2	40	-2440	<b>T9870-2440</b>	58	<b>T9871-2440</b>	83	44	<b>T9872-2440</b>	62	85
51	2	50	-3250	<b>T9870-3250</b>	58	<b>T9871-3250</b>	91	46	<b>T9872-3250</b>	67	95

### SUPERLOK

**T9876**  
(T987S)


SUPERSTAPLE  
O RING & BACK UP RING  
SUPPLIED



HOSE SIZE		STAPLE SIZE	DASH SIZE	SUPERLOK MALE	
DN	inch	inch		PART NO	C <sub>A</sub>
19	3/4	20	-1220	<b>T9876-1220</b>	48
25	1	25	-1625	<b>T9876-1625</b>	57
31	1.1/4	32	-2032	<b>T9876-2032</b>	71
38	1.1/2	40	-2440	<b>T9876-2440</b>	78
51	2	50	-3250	<b>T9876-3250</b>	83

### DIMENSIONS FOR SAE CODE 61 AND CODE 62 FLANGES, AND RYCO CODE 62C FLANGES

NOMINAL FLANGE	CODE 61				CODE 62				CODE 62C			
	B		T		B		T		B		T	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
1/2	30,2	1.19	6,73	0.265	31,8	1.25	7,75	0.305				
*5/8	34,0	1.34	6,73	0.265								
3/4	38,1	1.50	6,73	0.265	41,3	1.63	8,76	0.345	41,3	1.63	14,20	0.559
1	44,5	1.75	8,00	0.315	47,6	1.88	9,53	0.375	47,6	1.88	14,20	0.559
1.1/4	50,8	2.00	8,00	0.315	54,0	2.12	10,29	0.405	54,0	2.12	14,20	0.559
1.1/2	60,3	2.38	8,00	0.315	63,5	2.50	12,57	0.495	63,5	2.50	14,20	0.559
2	71,4	2.81	9,53	0.375	79,4	3.13	12,57	0.495	79,4	3.13	14,20	0.559
2.1/2	84,1	3.31	9,53	0.375								
3	101,6	4.00	9,53	0.375								



**NOTE:** \*5/8 is used by Komatsu.

RYCO Code 62C fittings conform to the flange OD and bolt hole patterns of SAE Code 62 but require special flange clamps. RYCO Code 62C flange heads are thicker than SAE Code 62 and measure T = 14,2 mm (0.559 inch) in all sizes.

# COUPLINGS

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS

### SAE FLANGE



**T9130**  
(T913)

**T9150**  
(T915)

**T9170**  
(T917)

**T9910**  
(T991)

RYCO  
CODE 61  
CLAMPS - SEE PAGES 345 & 346  
O RING NOT SUPPLIED



HOSE SIZE		NOM. FLANGE SIZE	DASH SIZE	CODE 61 FLANGE	CODE 61 FLANGE 45° TUBE BEND	CODE 61 FLANGE 90° TUBE BEND	CODE 61 FLANGE 110° TUBE BEND							
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9130-1212</b>	46	<b>T9150-1212</b>	68	26	<b>T9170-1212</b>	58	54			
25	1	1	-1616	<b>T9130-1616</b>	52	<b>T9150-1616</b>	83	30	<b>T9170-1616</b>	70	68			
25	1	1.1/4	-1620	<b>T9130-1620</b>	57	<b>T9150-1620</b>	85	32	<b>T9170-1620</b>	70	69			
31	1.1/4	1.1/4	-2020	<b>T9130-2020</b>	59	<b>T9150-2020</b>	99	36	<b>T9170-2020</b>	87	78			
31	1.1/4	1.1/2	-2024	<b>T9130-2024</b>	85	<b>T9150-2024</b>	102	38	<b>T9170-2024</b>	87	81			
38	1.1/2	1.1/2	-2424	<b>T9130-2424</b>	86	<b>T9150-2424</b>	116	42	<b>T9170-2424</b>	105	93	<b>T9910-2424</b>	148	107
38	1.1/2	2	-2432	<b>T9130-2432</b>	96	<b>T9150-2432</b>	121	47	<b>T9170-2432</b>	104	99	<b>T9910-2432</b>	147	115
51	2	2	-3232	<b>T9130-3232</b>	100	<b>T9150-3232</b>	154	58	<b>T9170-3232</b>	148	130	<b>T9910-3232</b>	166	136

NOTE: For SAE Code 61/62 and RYCO Code 62C Flange dimensions, see page 237.

### SAE FLANGE





**T9330**  
(T933)

**T9440**  
(T944)

**T9450**  
(T945)

**T9350**  
(T935)

RYCO  
CODE 62  
CLAMPS - SEE PAGES 345 & 346  
O RING NOT SUPPLIED



HOSE SIZE		NOM. FLANGE SIZE	DASH SIZE	CODE 62 FLANGE	CODE 62 FLANGE 22.5° TUBE BEND	CODE 62 FLANGE 30° TUBE BEND	CODE 62 FLANGE 45° TUBE BEND							
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9330-1212</b>	53	<b>T9440-1212</b>	80	16	<b>T9450-1212</b>	73	19	<b>T9350-1212</b>	69	28
19	3/4	1	-1216	<b>T9330-1216</b>	57							<b>T9350-1216</b>	73	31
25	1	3/4	-1612	<b>T9330-1612</b>	54									
25	1	1	-1616	<b>T9330-1616</b>	57	<b>T9440-1616</b>	91	16	<b>T9450-1616</b>	90	22	<b>T9350-1616</b>	84	31
25	1	1.1/4	-1620	<b>T9330-1620</b>	69				<b>T9450-1620</b>	90	25	<b>T9350-1620</b>	85	34
31	1.1/4	1	-2016	<b>T9330-2016</b>	68									
31	1.1/4	1.1/4	-2020	<b>T9330-2020</b>	69	<b>T9440-2020</b>	108	17	<b>T9450-2020</b>	108	22	<b>T9350-2020</b>	101	38
31	1.1/4	1.1/2	-2024	<b>T9330-2024</b>	98	<b>T9440-2024</b>	138	22	<b>T9450-2024</b>	113	25	<b>T9350-2024</b>	105	41
38	1.1/2	1.1/4	-2420	<b>T9330-2420</b>	70									
38	1.1/2	1.1/2	-2424	<b>T9330-2424</b>	100	<b>T9440-2424</b>	127	24	<b>T9450-2424</b>	135	33	<b>T9350-2424</b>	119	45
38	1.1/2	2	-2432	<b>T9330-2432</b>	118							<b>T9350-2432</b>	121	50
51	2	1.1/2	-3224	<b>T9330-3224</b>	105									
51	2	2	-3232	<b>T9330-3232</b>	122	<b>T9440-3232</b>	167	28	<b>T9450-3232</b>	165	40	<b>T9350-3232</b>	157	60


NOTE: For SAE Code 61/62 and RYCO Code 62C Flange dimensions, see page 237.

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS


### SAE FLANGE

**RYCO  
CODE 62  
CLAMPS - SEE PAGES 345 & 346  
O RING NOT SUPPLIED**


**T9460  
(T946)**




**T9360  
(T936)**



**T9370  
(T937)**



**T9930  
(T993)**




HOSE SIZE		NOM. FLANGE SIZE	DASH SIZE	CODE 62 FLANGE 60° TUBE BEND			CODE 62 FLANGE 67.5° TUBE BEND			CODE 62 FLANGE 90° TUBE BEND			CODE 62 FLANGE 110° TUBE BEND		
DN	inch	inch		PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9460-1212</b>	81	36	<b>T9360-1212</b>	80	47	<b>T9370-1212</b>	58	56			
19	3/4	1	-1216							<b>T9370-1216</b>	57	61			
25	1	3/4	-1612							<b>T9370-1612</b>	61	56			
25	1	1	-1616	<b>T9460-1616</b>	98	44	<b>T9360-1616</b>	91	51	<b>T9370-1616</b>	70	70			
25	1	1.1/4	-1620	<b>T9460-1620</b>	99	46	<b>T9360-1620</b>	95	72	<b>T9370-1620</b>	70	71			
31	1.1/4	1.1/4	-2020	<b>T9460-2020</b>	100	46	<b>T9360-2020</b>	134	72	<b>T9370-2020</b>	87	80	<b>T9930-2020</b>	89	97
31	1.1/4	1.1/2	-2024	<b>T9460-2024</b>	123	58	<b>T9360-2024</b>	138	74	<b>T9370-2024</b>	87	86			
38	1.1/2	1.1/2	-2424	<b>T9460-2424</b>	156	71				<b>T9370-2424</b>	105	98	<b>T9930-2424</b>	119	142
38	1.1/2	2	-2432	<b>T9460-2432</b>	160	79				<b>T9370-2432</b>	104	104	<b>T9930-2432</b>	143	122
51	2	2	-3232	<b>T9460-3232</b>	221	101				<b>T9370-3232</b>	165	131	<b>T9930-3232</b>	170	143

**NOTE:** For SAE Code 61/62 and RYCO Code 62C Flange dimensions, see page 237.


### SPECIAL FLANGE

**RYCO  
CODE 62C  
CLAMPS - SEE PAGES 345 & 346  
O RING NOT SUPPLIED**


**T9333  
(T933C)**




**T9443  
(T944C)**



**T9453  
(T945C)**



**T9353  
(T935C)**



HOSE SIZE		NOM. FLANGE SIZE	DASH SIZE	RYCO CODE 62C FLANGE			RYCO CODE 62C FLANGE 22.5° TUBE BEND			RYCO CODE 62C FLANGE 30° TUBE BEND			RYCO CODE 62C FLANGE 45° TUBE BEND		
DN	inch	inch		PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9333-1212</b>	88		<b>T9443-1212</b>	80	16	<b>T9453-1212</b>	84	23	<b>T9353-1212</b>	72	31
25	1	1	-1616	<b>T9333-1616</b>	90		<b>T9443-1616</b>	91	16	<b>T9453-1616</b>	111	24	<b>T9353-1616</b>	87	35
25	1	1.1/4	-1620	<b>T9333-1620</b>	90		<b>T9443-1620</b>	95	16	<b>T9453-1620</b>	114	25	<b>T9353-1620</b>	84	37
31	1.1/4	1.1/4	-2020	<b>T9333-2020</b>	87		<b>T9443-2020</b>	108	17	<b>T9453-2020</b>	116	25	<b>T9353-2020</b>	104	41
31	1.1/4	1.1/2	-2024	<b>T9333-2024</b>	87		<b>T9443-2024</b>	138	22	<b>T9453-2024</b>	115	26	<b>T9353-2024</b>	106	41
38	1.1/2	1.1/2	-2424	<b>T9333-2424</b>	89		<b>T9443-2424</b>	127	24	<b>T9453-2424</b>	117	30	<b>T9353-2424</b>	120	46
51	2	2	-3232	<b>T9333-3232</b>	110								<b>T9353-3232</b>	159	61

**NOTE:** These T9000C fittings have similar end styles to Caterpillar® XT-5 range of Flanged Hose Couplings. Cat™ Caterpillar®, XT-5™ Caterpillar®.

# COUPLINGS

## T9000 (T900) SERIES BITELOK ONE-PIECE CRIMP COUPLINGS

### SPECIAL FLANGE





**T9463**  
(T946C)

**T9363**  
(T936C)

**T9373**  
(T937C)

**T9933**  
(T993C)

RYCO  
CODE 62C  
CLAMPS - SEE PAGES 345 & 346  
O RING NOT SUPPLIED




HOSE SIZE		NOM. FLANGE SIZE	DASH SIZE	RYCO CODE 62C FLANGE 60° TUBE BEND	RYCO CODE 62C FLANGE 67.5° TUBE BEND	RYCO CODE 62C FLANGE 90° TUBE BEND	RYCO CODE 62C FLANGE 110° TUBE BEND								
DN	inch	inch		PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL	PART NO	C <sub>A</sub>	DL
19	3/4	3/4	-1212	<b>T9463-1212</b>	87	46	<b>T9363-1212</b>	82	52	<b>T9373-1212</b>	58	63			
25	1	1	-1616	<b>T9463-1616</b>	99	47	<b>T9363-1616</b>	94	53	<b>T9373-1616</b>	70	74			
25	1	1.1/4	-1620	<b>T9463-1620</b>	104	49	<b>T9363-1620</b>	95	56	<b>T9373-1620</b>	70	75			
31	1.1/4	1.1/4	-2020	<b>T9463-2020</b>	121	56	<b>T9363-2020</b>	114	67	<b>T9373-2020</b>	87	83			
31	1.1/4	1.1/2	-2024	<b>T9463-2024</b>	146	66	<b>T9363-2024</b>	137	76	<b>T9373-2024</b>	87	85			
38	1.1/2	1.1/2	-2424	<b>T9463-2424</b>	145	68	<b>T9363-2424</b>	137	77	<b>T9373-2424</b>	100	99	<b>T9933-2424</b>	141	120
51	2	2	-3232							<b>T9373-3232</b>	165	133			

**NOTE:** These **T9000C** fittings have similar end styles to Caterpillar® XT-5 range of Flanged Hose Couplings. Cat™ Caterpillar®, XT-5™ Caterpillar®.

### SALVAGE

**T9230**  
(T923)

TUBE WELD



HOSE SIZE		A	DASH SIZE	SALVAGE (LIFESAVER)	
DN	inch	inch		PART NO	C <sub>A</sub>
19	3/4	3/4	-1212	<b>T9230-1212</b>	23
25	1	1	-1616	<b>T9230-1616</b>	27
31	1.1/4	1.1/4	-2020	<b>T9230-2020</b>	31
38	1.1/2	1.1/2	-2424	<b>T9230-2424</b>	34
51	2	2	-3232	<b>T9230-3232</b>	48



**WARNING:** Due to high pressures involved, special care must be taken when using **T9230** Salvage Couplings. See Clause 8 of the Terms & Conditions of Sale.

### HAMMER UNION

**T91502**

**T91501**

FIGURE 1502  
STANDARD SERVICE



HOSE SIZE		THRD SIZE	DASH SIZE	FIG 1502 MALE (WITH NUT)	FIG 1502 FEMALE (WITH SEAL)		
DN	inch	inch		PART NO	C <sub>A</sub>	PART NO	C <sub>A</sub>
38	1.1/2	2	-2432	<b>T91502-2432</b>	111	<b>T91501-2432</b>	92
51	2	2	-3232	<b>T91502-3232</b>	115	<b>T91501-3232</b>	96

**NOTE:** Nut must be installed onto hose before coupling is installed and crimped. Replacement parts **RF1502N-32** nut and **RF1502W-32** Nitrile seal are available.

**NOTE:** Hose Compatibility for the **T9000** series can be found on page 234.