

HOSE

PRESSURE WASHER

TW1

TORNADO WASHER
ONE WIRE BRAID



RECOMMENDED FOR:

Hot Water Pressure Washer Machines.

TUBE:

Black, oil resistant synthetic rubber. Heat, cleaning chemicals and detergent resistant.

REINFORCEMENT:

One braid of high tensile steel wire.

COVER:

Grey synthetic rubber; oil, chicken fat and abrasion resistant. The cover of TW1 Hose is formulated to resist marking. No skiving required with T2000 Series BITELOK Crimp Couplings.

TEMPERATURE RANGE:

TW1 TORNADO WASHER Hose handles hot water up to +155°C (+310°F).
For water, emulsions etc. see page 57.








WORKING PRESSURE:

Maximum working pressures are based on 4:1 safety factor (maximum working pressure to minimum burst pressure).

COUPLINGS:

**BITELOK NON-SKIVE ONE-PIECE CRIMP
T2000 Series** (sizes -06 to -08)

Common hose couplings used on TW1 Hose include:
T2020S BSPP Female Live Swivel
T2940 PW Female
T2950 PW Gun Handle Tube.

TW1 – TORNADO WASHER HOSE															
PART NO	HOSE SIZE	NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES ONE PIECE	
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE
TW16	10	-06	9,5	3/8	17,4	0.69	210	3050	840	12200	60	2.4	0,34	0.23	T2000
TW18	12	-08	12,7	1/2	20,6	0.81	210	3050	840	12200	90	3.5	0,45	0.30	T2000