

Hose Type 3/2, 4/2, 6/2, 8/2



Applications

- Waterblast:** Heat exchanger tube cleaning
- Hydraulics:** Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks, hydraulic tools)



Technical Information

- Inner Core:** Polyoxymethylene (POM)
- Pressure Support:** 2 layers of high-tensile steel wire Polyamide (PA)
- Outer Cover:** 3/2 Green, 4/2 Green, 6/2 Green, 8/2 Green
- Colour:** -30°C to +60°C [-22°F to 140°F]
- Temperature:**

Type	Ø ID	Ø OD	Working Pressure	Burst Pressure	Bend Radius	Weight	Insert ID
3/2	3,4 mm	6,9 mm	1.000 bar	2.500 bar	60 mm	0,072 kg/m	2,0 mm
3/2	0,13 inch	0,27 inch	14.500 psi	36.250 psi	2,36 inch	0,048 lbs/ft	0,08 inch
4/2	4.0 mm	8,0 mm	1,200 bar	3,000 bar	75 mm	0,110 kg/m	2,5 mm
4/2	0,16 inch	0,31 inch	17.400 psi	43.500 psi	2.95 inch	0.074 lbs/ft	,10 inch
6/2	6.3 mm	11.5 mm	1.000 bar	2.500 bar	110 mm	0,175 kg/m	4,0 mm
6/2	0,25 inch	0,45 inch	14.500 psi	36.250 psi	4.33 inch	0.118 lbs/ft	.16 inch
8/2	8.1 mm	13.3 mm	840 bar	2.100 bar	130 mm	0,200 kg/m	5.5 mm
8/2	0,32 inch	0,52 inch	12,180 psi	30,450 psi	5.12 inch	0.134 lbs/ft	0,22 inch