Hose Type 8/8, 8MMUHP

SPIR STAR

Applications

Waterblast: Surface preparation (concrete removal, surface

cleaning of buildings, paint removal), tank and vessel cleaning, ultra high-pressure water jet cutting and hydro demolition (cutting and hydro demolition (cutting and demolition of armoured concrete,

pipelines, paper or steel)



Hydraulics:

Pressure test equipment (valves, tooling and control panels), hydraulic tools (instrumentation packages for gauges, control of service equipment, hydraulic jacks,

hydraulic tools)



Technical Information

Inner Core:

Pressure Support: Polyoxymethylene (POM)

Outer Cover: 8 layers of high-tensile steel wire

Colour: Polyamide (PA)

Temperature: 4/8 Dark Red, 8/mmUHP Chome Yellow

-30°C to +60°C [-22°F to 140°F]

Type	Ø ID	Ø OD	Working	Burst	Bend	Weight	Insert ID
4/8	4.0 mm	12,8	3,200 bar	8,000 bar	175 mm	0,540	1,8 mm
4/8	0,16 inch	0,50	46.400 psi	116.000	6.89 inch	0.363	0,07 inch
8/mmUHF	7.6 mm	22,0	3,200 bar	7.400 bar	300 mm	1,500	4.5 mm
8/mmUHF	9 0,30 inch	0,87	46,400 psi	107,300	11,81	1.008	0,18 inch