

3440

Moisture-Lok Hose



# Part Number	Hose Size	DN	Hose I.D.		Hose O.D.		Max. Operating Pressure		Burst Pressure		Min. Bend Radius		Weight	
			mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
3440-04	-04	6	6,4	0.25	13,2	0.52	190	2,750	758	11,000	32,0	1.25	0,09	0.06
3440-06	-06	10	9,5	0.38	16,6	0.66	155	2,250	620	9,000	51,0	2.00	0,13	0.09
3440-08	-08	12	12,7	0.50	20,6	0.81	138	2,000	552	8,000	76,0	3.00	0,18	0.12
3440-12	-12	19	19,0	0.75	29,0	1.14	103	1,500	414	6,000	127,0	5.00	0,36	0.24
3440-16	-16	25	25,4	1.00	37,0	1.46	103	1,500	414	6,000	203,0	8.00	0,55	0.37

Note: Always use accepted cleaning practices to clean finished hose assembly before use.

Construction:

Tube: Polyolefin

Reinforcement: Synthetic fiber

Cover: Perforated polyurethane

Operating Parameters:

Temperature Range

-23°C to +66°C

(-10°F to +150°F)

Applications:

- Conveying urethane foam components
- Moisture sensitive chemicals

Features:

- High moisture barrier core tube
- No plasticizers in the core tube
- UV resistant cover
- Custom colors available

Fitting Reference

903

90A Stainless

90H (-12 & -16)

90L Stainless (-12 & -16)