

34PW

Pure Water Hose



# Part Number	Hose Size	Hose I.D.		Hose O.D.		Max. Operating Pressure		Burst Pressure		Min. Bend Radius		Weight		Length		
		DN	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	m	ft
34PW-04-250BX	-04	6	6,4	0.25	13,2	0.52	190	2,750	758	11,000	32,0	1.25	0,09	0.06	76,2	250
34PW-06-250BX	-06	10	9,5	0.38	16,6	0.66	155	2,250	620	9,000	51,0	2.00	0,13	0.09	76,2	250
34PW-08-250BX	-08	12	12,7	0.50	20,6	0.81	138	2,000	552	8,000	76,0	3.00	0,24	0.16	76,2	250
34PW-12-250BX	-12	19	19,0	0.75	29,0	1.14	103	1,500	414	6,000	127,0	5.00	0,36	0.24	76,2	250
34PW-16-250BX	-16	25	25,4	1.00	37,0	1.46	103	1,500	414	6,000	203,0	8.00	0,55	0.37	76,2	250

Note: Always use accepted cleaning practices to clean finished hose assembly before use.

Construction:

Tube: Polyolefin

Reinforcement: Synthetic fiber

Cover: Blue, non-perforated polyurethane

Operating Parameters:

Temperature Range

-23°C to +66°C
(-10°F to +150°F)

Applications:

- Pure water transfer
- Deionized water
- Distilled water
- Potable water
- Food products

Features:

- Made with NSF approved materials
- Core tube is free of plasticizers
- Prevents moisture transmission, extraction of contaminants
- Long lengths available

Agency Listings:

U.S. Navy
(MIL-STD-767A Ships)
NSF-51 and NSF-61 Certified

Fitting Reference

90A Stainless

90L Stainless (-12 & -16)