

# CNG FLEX HOSE

## Convert and Conserve

**THE ULTIMATE PTFE HOSE FOR CNG USED BY AUTOMOTIVE MANUFACTURERS, CONVERTERS AND FILLING STATION OPERATIONS.**

- 117198 hose is certified by CSA certificate no. 1133929
- PTFE innercore withstands temperature extremes\*
- High-pressure stainless steel reinforcement for reliable performance
- Special abrasion-resistant cover protects hose from wear
- Different end fittings adapted to your conversion available

### APPLICATIONS:

- Automotive and van fleets
- Truck and bus conversions
- Portable and stationary engines
- Dispensers



### HOSE DIMENSIONS AND PRESSURE RATINGS

HOSEPART NUMBER	NOMINAL SIZE	NOMINAL SIZE	NOMINAL ID	NOMINAL OD	CSA SERVICE PRESSURE	MAX OPERATING PRESSURE†	BURST PRESSURE ROOM TEMP	MAXIMUM CONTINUOUS LENGTH	MINIMUM BEND	HOSE WEIGHT
	in	mm	in	in	psi	psi	psi	ft	in	lb/ft
117198-4	1/4	6	.222	.390	3,600	5,000	16,000	50	1.50	.118
117198-6	3/8	10	.308	.490	3,600	5,000	16,000	50	2.50	.184
117198-8	1/2	13	.401	.615	3,600	5,000	16,000	38	2.87	.261

† Operating pressure shown are for non-impulsive service.