



R272 HOSE

APPLICATIONS:

- Chemical processing
- Pulp and paper
- Foam packaging
- Turbine engine componentry
- Air compressor discharge
- Tire press

TEMPERATURE RANGE:

- -65° F to 400° F (-54° to 204° C)

Consult factory for dynamic flexing applications at temperature limits and temperature adjusted pressure rating

AVAILABILITY:

Convoluted PTFE can be fitted and tested to your exact specification. Kord Industrial is certified to fabricate and distribute all Titeflex convoluted R272 series hose assemblies.

Rapid response and same day shipping is always available from a large on-site inventory.

Unmatched engineering and technical experience in the application of convoluted PTFE hose products has allowed users to consistently rely on Titeflex for dependable performance and value every time.

Titeflex R272 hose is extremely flexible and lightweight offering an improved alternative to maximize operator handling and safety in comparison to other types of industrial hose. Combined with PTFE's unmatched chemical compatibility, corrosion resistance, temperature range and "non-stick" attributes, it offers a superior value.

R272 HOSE CONSTRUCTION:

A white non-conductive PTFE liner, externally reinforced with PTFE impregnated fiberglass and a single steel wire braid.

END FITTING ATTACHMENTS:

R272 series hose fitting selections include male pipe, JIC female swivel, sanitary flange and flange retainer ends to support use of 150# and 300# ANSI lap joint flange.

Fitting materials available are plated carbon steel, 316 SS, and an optional PTFE coated flange retainer

The hose ends are permanently attached by either swaging or crimping, depending on end style selected.

Please see Hose End Catalog for complete fitting selection and specifications.

R272 HOSE SPECIFICATIONS

HOSE PART NUMBER	NOMINAL SIZE		NOMINAL ID	NOMINAL OD	OPERATING PRESSURE	BURST PRESSURE ROOM TEMP	MAXIMUM CONTINUOUS LENGTH	MINIMUM BEND RADIUS @ ROOM TEMP	HOSE WEIGHT
	in	mm	in	in	psi	psi	ft	in	lb/ft
R272-8	1/2	13	.512	.785	1,000	4,000	75	1.00	.22
R272-12	3/4	19	.750	1.060	1,000	4,000	50	2.00	.29
R272-16	1	25	.998	1.280	1,000	4,000	50	3.00	.41
R272-20	1-1/4	32	1.239	1.525	1,000	3,600	50	6.25	.50
R272-24	1-1/2	38	1.500	1.802	750	3,000	50	7.50	.62
R272-32	2	51	1.982	2.305	500	2,000	50	10.00	.97



These products can be used to convey hazardous fluids, steam, and other dangerous materials which can cause personal injury or property damage if released through misuse, misapplication, or damaged. The user is responsible to analyze each application prior to specifying any product from this catalog. Due to the wide variety of operating conditions and applications, the user, through personal analysis and testing, is solely responsible for final product selection and meeting all performance, safety, and warning requirements. Careful selection, proper assembly and use of hose fittings and accessories is essential for the safe and warranted operation of the hose assembly.